



SPECIFIKACIJE

OKVIR	
VELIČINE	27.5": XS, S, M 29": S, M, L
BOJE	Matte Black / Gloss Sparkling Black
OKVIR	ALUXX-Grade Aluminum, 120mm FlexPoint Suspension
VILICA	Giant Crest 34 SL RCL, 130mm, 15x110
AMORTIZER	RockShox Monarch R, 184.15/44.45, custom tuned for Liv
KOMPONENTE	
VOLAN	Giant Connect Trail, Alloy For 27.5: XS:730mm, S:750mm, M:750mm For 29: S:750mm, M:750mm, L:780mm
GRIPS	Giant Sole-O
LULA VOLANA	Giant Contact For 27.5: XS:40mm, S:50mm, M:50mm For 29: S:50mm, M:50mm, L:60mm
CIJEV SJEDALA	Giant Contact Switch dropper, remote For 27.5: XS: 75mm travel / 30.9 x 295mm S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm For 29: S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 395mm
SJEDALO	Liv Sylvia
PEDALE	N/A
POGON	
RUČICE MJENJAČA	SRAM SX Eagle, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM SX Eagle
KOČNICE	Tektro, hydraulic, Tektro 6 bolt rotors [F]180mm, [R]160mm
RUČICE KOČNICA	Tektro, hydraulic
KAZETA	SRAM SX Eagle, 11x50
LANAC	SRAM SX Eagle
POGON	SRAM SX Eagle DUB, 30t For 27.5: XS:165mm, S:170mm, M:170mm For 29: S:170mm, M:170mm, L:170mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	"For 27.5: Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width For 29: Giant AM 29, tubeless ready, sleeve-joint rim, 30mm inner width"
NABE	alloy, loose ball
ŽBICE	Sapim
GUME	For 27.5: [F] Maxxis Rekon 27.5x2.6 WT, EXO, TR, tubeless [R] Maxxis Ardent Race 27.5x2.6 WT, EXO, TR, tubeless For 29: [F/R] Maxxis Forecaster 29x2.35 WT, EXO, TR, tubeless
DODACI	For 27.5: tubeless prepared, max tire size 2.6", max chainring size 32t For 29: tubeless prepared, max tire size 2.4", max chainring size 32t

GEOMETRIJA

OKVIR	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")
Dužina cijevi sjedala (mm)	380	406	405	445	420	440
Kut cijevi sjedala	74,0°	74,0°	76,0°	74,0°	76,0°	76,0°
Dužina gornje cijevi (mm)	565	580	565	595	585	605
Dužina prednje cijevi (mm)	95	100	105	110	115	125
Kut vilice	67,5°	67,5°	67,0°	67,5°	67,0°	67,0°
Zakrivljenost vilice (offset) (mm)	43	43	51	43	51	51
Staza (mm)	103,6	103,6	105,3	103,6	105,3	105,3
Međuosovinski razmak kotača (mm)	1109	1125	1147	1141	1169	1190
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	435	435	438	435	438	438
Položaj osovine pogona (mm)	20	20	40	20	40	40
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	560	565	614	574	623	632
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	404	418	412	430	430	447
Prekoračna visina (mm)	690	705	712	733	734	755
Širina volana (mm)	750	750	740	780	760	780
Dužina lule volana (mm)	40	40	40	50	50	50
Dužina poluge pedale (mm)	165	170	170	170	170	170
Veličina kotača	27.5"	27.5"	29"	27.5"	29"	29"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.