



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	27.5": XS, S, M 29": S, M, L
FARBY	Matte Black / Gloss Sparkling Black
RÁM	ALUXX-Grade Aluminum, 120mm FlexPoint Suspension
VIDLICA	Giant Crest 34 SL RCL, 130mm, 15x110
TLMIČ	RockShox Monarch R, 184.15/44.45, custom tuned for Liv
KOMPONENTY	
RIADIDLÁ	Giant Connect Trail, Alloy For 27.5: XS:730mm, S:750mm, M:750mm For 29: S:750mm, M:750mm, L:780mm
GRIPY	Giant Sole-O
PREDSTAVEC	Giant Contact For 27.5: XS:40mm, S:50mm, M:50mm For 29: S:50mm, M:50mm, L:60mm
SEDLOVKA	Giant Contact Switch dropper, remote For 27.5: XS: 75mm travel / 30.9 x 295mm S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm For 29: S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 395mm
SEDADLO	Liv Sylvia
PEDÁLE	N/A
POHON	
RADENIE	SRAM SX Eagle, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	SRAM SX Eagle
BRZDY	Tektro, hydraulic, Tektro 6 bolt rotors [F]180mm, [R]160mm
BRZDOVÉ PÁKY	Tektro, hydraulic
KAZETA	SRAM SX Eagle, 11x50
REŤAZ	SRAM SX Eagle
KLUKY	SRAM SX Eagle DUB, 30t For 27.5: XS:165mm, S:170mm, M:170mm For 29: S:170mm, M:170mm, L:170mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	"For 27.5: Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width For 29: Giant AM 29, tubeless ready, sleeve-joint rim, 30mm inner width"
NÁBOJE	alloy, loose ball
ŠPICE	Sapim
PNEUMATIKY	For 27.5: [F] Maxxis Rekon 27.5x2.6 WT, EXO, TR, tubeless [R] Maxxis Ardent Race 27.5x2.6 WT, EXO, TR, tubeless For 29: [F/R] Maxxis Forecaster 29x2.35 WT, EXO, TR, tubeless
DOPLNKY	For 27.5: tubeless prepared, max tire size 2.6", max chainring size 32t For 29: tubeless prepared, max tire size 2.4", max chainring size 32t

Cena: nová cena 1 919 € (stará cena 2 549 €)

GEOMETRIA

RÁM	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")
Dĺžka sedlovej trubky (mm)	380	406	405	445	420	440
Uhol sedlovej trubky	74,0°	74,0°	76,0°	74,0°	76,0°	76,0°
Dĺžka hornej rámovej trubky (mm)	565	580	565	595	585	605
Dĺžka hlavovej trubky (mm)	95	100	105	110	115	125
Uhol hlavovej trubky	67,5°	67,5°	67,0°	67,5°	67,0°	67,0°
Offset vidlice (mm)	43	43	51	43	51	51
Trail (mm)	103,6	103,6	105,3	103,6	105,3	105,3
Rázvor (mm)	1109	1125	1147	1141	1169	1190
Dĺžka zadnej stavby (mm)	435	435	438	435	438	438
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	20	20	40	20	40	40
Stack - výška riadenia (mm)	560	565	614	574	623	632
Reach (mm)	404	418	412	430	430	447
Výška rámu od zeme (mm)	690	705	712	733	734	755
Šírka riaditok (mm)	750	750	740	780	760	780
Dĺžka predstavca (mm)	40	40	40	50	50	50
Dĺžka klúku (mm)	165	170	170	170	170	170
Rozmer kolies	27.5"	27.5"	29"	27.5"	29"	29"

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.