



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	For 27.5": XS, S, M, For 29": S, M, L
COULEURS	Chrysocola, Cold Night
CADRE	ALUXX-grade aluminum, 120mm FlexPoint Suspension
FOURCHE	Giant STL 34, 140mm, Boost 15x110
AMORTISSEUR (SHOCK)	Suntour Raidon R, 184x44, custom tuned for Liv
COMPOSANTES	
GUIDON	Giant Contact TR35, 20mm rise, alloy 27.5": XS: 730mm, S: 750mm, M: 750mm 29": S: 750mm, M: 750mm, L: 780mm
POIGNÉES	Giant Sole-O
POTENCE	Giant Contact, 35mm 27.5": XS: 40mm, S: 50mm, M: 50mm 29": S: 50mm, M: 50mm, L: 60mm
TIGE DE SELLE	Giant Contact Switch dropper, remote 27.5": XS: 75mm travel / 30.9 x 295mm S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm 29": S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 345mm
SELLE	Liv Sylvia
PÉDALES	platform
TRANSMISSION (DRIVETRAIN)	
LEVIERS DE VITESSE	Shimano CUES SL-6000, 1x10
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano CUES RD-U6000, Shadow +
FREINS	Shimano BR-MT200, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
LEVIERS DE FREIN	Shimano BL-MT201
CASSETTE	Shimano CUES CS-LG300, 11x48
CHAÎNE	Shimano CUES LG500
PÉDALIER	Shimano CUES, FC-U6000-1, 30t 27.5": XS: 170mm, S: 170mm, M: 170mm Praxis Cadet Boost, 30t 29": S: 170mm, M: 170mm, L: 170mm
BOÎTIER DE PÉDALIER	Shimano BB MT501, press fit

ROUES	
JANTES	27.5": Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width 29": Giant AM 29, tubeless ready, sleeve-joint rim, 30mm inner width
MOYEUX	alloy
RAYONS	Sapim
PNEUS	27.5": [F] Maxxis Minion DHF 27.5x2.6, EXO, TR, tubeless [R] Maxxis Dissector 27.5x2.6, EXO, TR, tubeless 29": [F] Maxxis Minion DHF 29x2.5 WT, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4 WT, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.6", max chainring size 32t

Prix de détail: 2 299,00 \$

GÉOMÉTRIE

CADRE	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")
Longueur du tube de selle (mm)	380	406	405	445	420	440
Seat Post Insertion Depth (mm)	145	170	220	210	235	255
Angle du tube de selle	74,0°	74,0°	76,0°	74,0°	76,0°	76,0°
Longueur du tube supérieur (top tube) (mm)	565	580	565	595	585	605
Longueur du tube de direction (head tube) (mm)	95	100	105	110	115	125
Angle du tube de direction	67,5°	67,5°	67,0°	67,5°	67,0°	67,0°
Déport (rake) de fourche (mm)	43	43	51	43	51	51
Trail (mm)	103,6	103,6	105,3	103,6	105,3	105,3
Empattement (mm)	1109	1125	1147	1141	1169	1190
Longueur des bases (mm)	435	435	438	435	438	438
Hauteur du boîtier de pédalier (mm)	20	20	40	20	40	40
Portée Verticale (Stack) (mm)	560	565	614	574	623	632
Portée Horizontale (Reach) (mm)	404	418	412	430	430	447
Hauteur du cadre (mm)	690	705	712	733	734	755
Largeur du Guidon (mm)	750	750	740	780	760	780
Longueur de la Potence (mm)	40	40	40	50	50	50
Longueur des manivelles (mm)	165	170	170	170	170	170
Diamètre des Roues	27.5"	27.5"	29"	27.5"	29"	29"

Giant Canada se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.