



TECHNIQUES

CADRE	
TAILLES	27.5": XS, S, M 29": S, M, L
COLORIS	Milky Way
CADRE	ALUXX-Grade Aluminum, 120mm FlexPoint Suspension
FOURCHE	Giant Crest 34 RCL, 130mm, 15x110
AMORTISSEUR	Suntour Raidon R, 184.15/44.45, custom tuned for Liv
COMPOSANTS	
CINTRE	Giant Connect Trail, alloy For 27.5: XS:730mm, S:750mm, M:750mm For 29: S:750mm, M:750mm, L:780mm
POIGNÉES	Giant Sole-O
POTENCE	Giant Contact For 27.5: XS:40mm, S:50mm, M:50mm For 29: S:50mm, M:50mm, L:60mm
TIGE DE SELLE	Giant Contact Switch dropper, remote For 27.5: XS: 75mm travel / 30.9 x 295mm S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm For 29: S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 395mm
SELLE	Liv Sylvia
PÉDALES	platform
DÉRAILLEUR	
MANETTES	Shimano Deore M4100, 1x10
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano Deore M5120
FREINS	Tektro MD-M280 hydraulic, Shimano SM-RT26 6 bolt rotors
LEVIERS DE FREIN	Shimano BL-MT201
CASSETTE	Shimano Deore M4100, 11x46
CHAÎNE	KMC X-10
PÉDALIER	Praxis Cadet Boost, 30t For 27.5: XS:165mm, S:170mm, M:170mm For 29: S:170mm, M:170mm, L:170mm
BOITIER DE PÉDALIER	Praxis, press fit

ROUES	
JANTES	For 27.5: Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width For 29: Giant AM 29, tubeless ready, sleeve-joint rim, 30mm inner width
MOYEURS	DM RS02F/ED260R
RAYONS	Sapim
PNEUS	For 27.5: [F] Maxxis Rekon 27.5x2.6 WT, EXO, TR, tubeless [R] Maxxis Ardent Race 27.5x2.6 WT, EXO, TR, tubeless For 29: [F/R] Maxxis Forecaster 29x2.35 WT, EXO, TR, tubeless
EXTRAS	For 27.5: tubeless prepared, max tire size 2.6", max chainring size 32t For 29: tubeless prepared, max tire size 2.4", max chainring size 32t
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 1 750,00 €

GÉOMÉTRIE

CADRE	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")
Longueur de tube de selle (mm)	380	406	405	445	420	440
Angle de tube de selle	74,0°	74,0°	76,0°	74,0°	76,0°	76,0°
Longueur du tube supérieur (mm)	565	580	565	595	585	605
Longueur du tube de direction (mm)	95	100	105	110	115	125
Angle du tube de direction	67,5°	67,5°	67,0°	67,5°	67,0°	67,0°
Déport de fourche (mm)	43	43	51	43	51	51
Trail (mm)	103,6	103,6	105,3	103,6	105,3	105,3
Empattement (mm)	1109	1125	1147	1141	1169	1190
Longueur des bases (mm)	435	435	438	435	438	438
Drop du boîtier de pédalier (mm)	20	20	40	20	40	40
Stack (mm)	560	565	614	574	623	632
Reach (mm)	404	418	412	430	430	447
Hauteur en statique (mm)	690	705	712	733	734	755
Largeur de cintre (mm)	750	750	740	780	760	780
Longueur de potence (mm)	40	40	40	50	50	50
Longueur des manivelles (mm)	165	170	170	170	170	170
Diamètre des roues	27.5"	27.5"	29"	27.5"	29"	29"

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.