



SPECIFIKACIJE

OKVIR	
VELIČINE	For 27.5": XS, S, M, For 29": S, M, L
BOJE	Chrysocolla, Cold Night
OKVIR	ALUXX-grade aluminum, 120mm FlexPoint Suspension
VILICA	Giant STL 34, 140mm, Boost 15x110
AMORTIZER	Suntour Raidon R, 184x44, custom tuned for Liv
KOMPONENTE	
VOLAN	Giant Contact TR35, 20mm rise, alloy 27.5": XS: 730mm, S: 750mm, M: 750mm 29": S: 750mm, M: 750mm, L: 780mm
GRIPS	Giant Sole-O
LULA VOLANA	Giant Contact, 35mm 27.5": XS: 40mm, S: 50mm, M: 50mm 29": S: 50mm, M: 50mm, L: 60mm
CIJEV SJEDALA	Giant Contact Switch dropper, remote 27.5": XS: 75mm travel / 30.9 x 295mm S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm 29": S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 345mm
SJEDALO	Liv Sylvia
PEDALE	platform
POGON	
RUČICE MJENJAČA	Shimano CUES SL-6000, 1x10
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	Shimano CUES RD-U6000, Shadow +
KOČNICE	Shimano BR-MT200, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
RUČICE KOČNICA	Shimano BL-MT201
KAZETA	Shimano CUES CS-LG300, 11x48
LANAC	Shimano CUES LG500
POGON	Shimano CUES, FC-U6000-1, 30t 27.5": XS: 170mm, S: 170mm, M: 170mm Praxis Cadet Boost, 30t 29": S: 170mm, M: 170mm, L: 170mm
OSOVINA POGONA (BB)	Shimano BB MT501, press fit

KOTAČI	
OBRUČI	27.5": Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width 29": Giant AM 29, tubeless ready, sleeve-joint rim, 30mm inner width
NABE	alloy
ŽBICE	Sapim
GUME	27.5": [F] Maxxis Minion DHF 27.5x2.6, EXO, TR, tubeless [R] Maxxis Dissector 27.5x2.6, EXO, TR, tubeless 29": [F] Maxxis Minion DHF 29x2.5 WT, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4 WT, EXO, TR, tubeless
DODACI	tubeless prepared, max tire size 2.6", max chainring size 32t

GEOMETRIJA

OKVIR	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (27.5")
Dužina cijevi sjedala (mm)	380	406	405	445	420	490
Seat Post Insertion Depth (mm)	145	170	220	210	235	255
Kut cijevi sjedala	74,0°	74,0°	76,0°	74,0°	76,0°	74,0°
Dužina gornje cijevi (mm)	565	580	565	595	585	610
Dužina prednje cijevi (mm)	95	100	105	110	115	120
Kut vilice	67,5°	67,5°	67,0°	67,5°	67,0°	67,5°
Zakrivljenost vilice (offset) (mm)	43	43	51	43	51	43
Staza (mm)	103,6	103,6	105,3	103,6	105,3	103,6
Međuosovinski razmak kotača (mm)	1109	1125	1147	1141	1169	1157
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	435	435	438	435	438	435
Položaj osovine pogona (mm)	20	20	40	20	40	20
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	560	565	614	574	623	583
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	404	418	412	430	430	442
Prekoračna visina (mm)	690	705	712	733	734	759
Širina volana (mm)	750	750	740	780	760	780
Dužina lule volana (mm)	40	40	40	50	50	50
Dužina poluge pedale (mm)	165	170	170	170	170	175
Veličina kotača	27.5"	27.5"	29"	27.5"	29"	27.5"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.