



SPECS

CADRU	
MARIMI	For 27.5": XS, S, M, For 29": S, M, L
CULORI	Chrysocola, Cold Night
CADRU	ALUXX-grade aluminum, 120mm FlexPoint Suspension
FURCA	Giant STL 34, 140mm, Boost 15x110
SOC	Suntour Raidon R, 184x44, custom tuned for Liv
COMPONENTE	
GHIDON	Giant Contact TR35, 20mm rise, alloy 27.5": XS: 730mm, S: 750mm, M: 750mm 29": S: 750mm, M: 750mm, L: 780mm
GRIPS	Giant Sole-O
PIPA	Giant Contact, 35mm 27.5": XS: 40mm, S: 50mm, M: 50mm 29": S: 50mm, M: 50mm, L: 60mm
TIJA SA	Giant Contact Switch dropper, remote 27.5": XS: 75mm travel / 30.9 x 295mm S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm 29": S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 345mm
SA	Liv Sylvia
PEDALE	platform
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano CUES SL-6000, 1x10
SCHIMBATOR FATA	N/A
SCHIMBATOR SPATE	Shimano CUES RD-U6000, Shadow +
FRANE	Shimano BR-MT200, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
MANETE FRANA	Shimano BL-MT201
PINIOANE	Shimano CUES CS-LG300, 11x48
LANT	Shimano CUES LG500
ANGRENAJ	Shimano CUES, FC-U6000-1, 30t 27.5": XS: 170mm, S: 170mm, M: 170mm Praxis Cadet Boost, 30t 29": S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Shimano BB MT501, press fit

ROTI	
JANTE	27.5": Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width 29": Giant AM 29, tubeless ready, sleeve-joint rim, 30mm inner width
BUTUCI	alloy
SPITE	Sapim
ANVELOPE	27.5": [F] Maxxis Minion DHF 27.5x2.6, EXO, TR, tubeless [R] Maxxis Dissector 27.5x2.6, EXO, TR, tubeless 29": [F] Maxxis Minion DHF 29x2.5 WT, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4 WT, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.6", max chainring size 32t

GEOMETRIE

CADRU	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (27.5")	L (29")
Seat Tube Length (mm)	380	406	405	445	420	490	440
Seat Post Insertion Depth (mm)	145	170	220	210	235	255	255
Seat Tube Angle	74,0°	74,0°	76,0°	74,0°	76,0°	74,0°	76,0°
Top Tube Length (mm)	565	580	565	595	585	610	605
Head Tube Length (mm)	95	100	105	110	115	120	125
Head Tube Angle	67,5°	67,5°	67,0°	67,5°	67,0°	67,5°	67,0°
Fork Rake (mm)	43	43	51	43	51	43	51
Trail (mm)	103,6	103,6	105,3	103,6	105,3	103,6	105,3
Wheelbase (mm)	1109	1125	1147	1141	1169	1157	1190
Chain Stay Length (mm)	435	435	438	435	438	435	438
Bottom Bracket Drop (mm)	20	20	40	20	40	20	40
Stack (mm)	560	565	614	574	623	583	632
Reach (mm)	404	418	412	430	430	442	447
Stand Over Height (mm)	690	705	712	733	734	759	755
Handlebar Width (mm)	750	750	740	780	760	780	780
Stem Length (mm)	40	40	40	50	50	50	50
Crank Length (mm)	165	170	170	170	170	175	170
Wheel Size	27.5"	27.5"	29"	27.5"	29"	27.5"	29"

Toate specificatiile enumerate se pot schimba fara notificare prealabila.