



## SPECIFIKACIJE

OKVIR	
VELIKOSTI	27.5": XS, S, M 29": S, M, L
BARVE	Milky Way, Purple Ash
OKVIR	ALUXX-Grade Aluminum, 120mm FlexPoint Suspension
VILICE	Giant Crest 34 RCL, 130mm, 15x110
AMORTIZER	Suntour Raidon R, 184.15/44.45
KOMPONENTE	
KRMILO	Giant Connect Trail, alloy For 27.5: XS:730mm, S:750mm, M:750mm For 29: S:750mm, M:750mm, L:780mm
GRIPS	Giant Sole-O
OPORA KRMILA	Giant Contact For 27.5: XS:40mm, S:50mm, M:50mm For 29: S:50mm, M:50mm, L:60mm
OPORA SEDEŽA	Giant Contact Switch dropper, remote For 27.5: XS: 75mm travel / 30.9 x 295mm S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm For 29: S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 395mm
SEDEŽ	Liv Sylvia
PEDALA	platform
POGON	
PRESTAVNE ROČICE	Shimano Deore M4100, 1x10
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano Deore M5120
ZAVORE	Shimano BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Shimano BL-MT201
VERIŽNIK	Shimano Deore M4100, 11x46
VERIGA	KMC X-10
GONILKE Z VERIŽNIKI	Praxis Cadet Boost, 30t For 27.5: XS:165mm, S:170mm, M:170mm For 29: S:170mm, M:170mm, L:170mm
BOTTOM BRACKET	Praxis, press fit

OBROČNIKI	
OBROČI	For 27.5: Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width For 29: Giant AM 29, tubeless ready, sleeve-joint rim, 30mm inner width
PESTA	alloy, loose ball
NAPERE	Sapim
PLAŠČI	For 27.5: [F] Maxxis Rekon 27.5x2.6 WT, EXO, TR, tubeless [R] Maxxis Ardent Race 27.5x2.6 WT, EXO, TR, tubeless For 29: [F/R] Maxxis Forecaster 29x2.35 WT, EXO, TR, tubeless
DODATKI	For 27.5: tubeless prepared, max tire size 2.6", max chainring size 32t For 29: tubeless prepared, max tire size 2.4", max chainring size 32t

## GEOMETRIJA

OKVIR	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")
Dolžina sedežne cevi (mm)	380	406	405	445	420	440
Kot sedežne cevi	74,0°	74,0°	76,0°	74,0°	76,0°	76,0°
Top Tube Length (mm)	565	580	565	595	585	605
Višina glave okvirja (mm)	95	100	105	110	115	125
Krmlini kot	67,5°	67,5°	67,0°	67,5°	67,0°	67,0°
Zamik vpetja osi (mm)	43	43	51	43	51	51
Trail (mm)	103,6	103,6	105,3	103,6	105,3	105,3
Medosna razdalja (mm)	1109	1125	1147	1141	1169	1190
Dolžina cevi ob verigi (mm)	435	435	438	435	438	438
Bottom Bracket Drop (mm)	20	20	40	20	40	40
Oddaljenost zgornje cevi od gonilne osi (mm)	560	565	614	574	623	632
Doseg (mm)	404	418	412	430	430	447
Višina zgornje cevi (mm)	690	705	712	733	734	755
Širina krmila (mm)	750	750	740	780	760	780
Dolžina opore krmila (mm)	40	40	40	50	50	50
Dolžina gonilke (mm)	165	170	170	170	170	170
Velikost obročnikov	27.5"	27.5"	29"	27.5"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.