



SPECIFIKACIJE

OKVIR	
VELIKOSTI	For 27.5": XS, S, M, For 29": S, M, L
BARVE	Chrysocola, Cold Night
OKVIR	ALUX-grade aluminum, 120mm FlexPoint Suspension
VILICE	Giant STL 34, 140mm, Boost 15x110
AMORTIZER	Suntour Raidon R, 184x44, custom tuned for Liv
KOMPONENTE	
KRMILO	Giant Contact TR35, 20mm rise, alloy 27.5": XS: 730mm, S: 750mm, M: 750mm 29": S: 750mm, M: 750mm, L: 780mm
GRIPS	Giant Sole-O
OPORA KRMILA	Giant Contact, 35mm 27.5": XS: 40mm, S: 50mm, M: 50mm 29": S: 50mm, M: 50mm, L: 60mm
OPORA SEDEŽA	Giant Contact Switch dropper, remote 27.5": XS: 75mm travel / 30.9 x 295mm S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm 29": S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 345mm
SEDEŽ	Liv Sylvia
PEDALA	platform
POGON	
PRESTAVNE ROČICE	Shimano CUES SL-6000, 1x10
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano CUES RD-U6000, Shadow +
ZAVORE	Shimano BR-MT200, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
ZAVORNE ROČICE	Shimano BL-MT201
VERIŽNIK	Shimano CUES CS-LG300, 11x48
VERIGA	Shimano CUES LG500
GONILKE Z VERIŽNIKI	Shimano CUES, FC-U6000-1, 30t 27.5": XS: 170mm, S: 170mm, M: 170mm Praxis Cadet Boost, 30t 29": S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Shimano BB MT501, press fit

OBROČNIKI	
OBROČI	27.5": Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width 29": Giant AM 29, tubeless ready, sleeve-joint rim, 30mm inner width
PESTA	alloy
NAPERRE	Sapim
PLAŠČI	27.5": [F] Maxxis Minion DHF 27.5x2.6, EXO, TR, tubeless [R] Maxxis Dissector 27.5x2.6, EXO, TR, tubeless 29": [F] Maxxis Minion DHF 29x2.5 WT, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4 WT, EXO, TR, tubeless
DODATKI	tubeless prepared, max tire size 2.6", max chainring size 32t

GEOMETRIJA

OKVIR	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (27.5")	L (29")
Dolžina sedežne cevi (mm)	380	406	405	445	420	490	440
Seat Post Insertion Depth (mm)	145	170	220	210	235	255	255
Kot sedežne cevi	74,0°	74,0°	76,0°	74,0°	76,0°	74,0°	76,0°
Top Tube Length (mm)	565	580	565	595	585	610	605
Višina glave okvirja (mm)	95	100	105	110	115	120	125
Krmilni kot	67,5°	67,5°	67,0°	67,5°	67,0°	67,5°	67,0°
Zamik vpetja osi (mm)	43	43	51	43	51	43	51
Trail (mm)	103,6	103,6	105,3	103,6	105,3	103,6	105,3
Medosna razdalja (mm)	1109	1125	1147	1141	1169	1157	1190
Dolžina cevi ob verigi (mm)	435	435	438	435	438	435	438
Bottom Bracket Drop (mm)	20	20	40	20	40	20	40
Oddaljenost zgornje cevi od gonilne osi (mm)	560	565	614	574	623	583	632
Doseg (mm)	404	418	412	430	430	442	447
Višina zgornje cevi (mm)	690	705	712	733	734	759	755
Širina krmila (mm)	750	750	740	780	760	780	780
Dolžina opore krmila (mm)	40	40	40	50	50	50	50
Dolžina gonilke (mm)	165	170	170	170	170	175	170
Velikost obročnikov	27.5"	27.5"	29"	27.5"	29"	27.5"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.