

# EMBOLDEN 2



## SPECS

RAM	
STORLEKAR	For 27.5": XS, S, M, For 29": S, M, L
FÄRGER	Chrysocolla, Cold Night
RAM	ALUXX-grade aluminum, 120mm FlexPoint Suspension
GAFFEL	Giant STL 34, 140mm, Boost 15x110
BAKDÄMPARE	Suntour Raidon R, 184x44, custom tuned for Liv
KOMPONENTER	
STYRE	Giant Contact TR35, 20mm rise, alloy 27.5": XS: 730mm, S: 750mm, M: 750mm 29": S: 750mm, M: 750mm, L: 780mm
GREPPAR	Giant Sole-O
STAM	Giant Contact, 35mm 27.5": XS: 40mm, S: 50mm, M: 50mm 29": S: 50mm, M: 50mm, L: 60mm
SADELSTOLPE	Giant Contact Switch dropper, remote 27.5": XS: 75mm travel / 30.9 x 295mm S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm 29": S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 345mm
SADEL	Liv Sylvia
PEDALER	platform
DRIVLINJA	
VÄXLAR	Shimano CUES SL-6000, 1x10
FRAMVÄXEL	N/A
BAKVÄXEL	Shimano CUES RD-U6000, Shadow +
BROMSAR	Shimano BR-MT200, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
BROMSSPAKAR	Shimano BL-MT201
KASSETT	Shimano CUES CS-LG300, 11x48
KEDJA	Shimano CUES LG500
VEVPARTI	Shimano CUES, FC-U6000-1, 30t 27.5": XS: 170mm, S: 170mm, M: 170mm Praxis Cadet Boost, 30t 29": S: 170mm, M: 170mm, L: 170mm
BROMSREGLAGE	Shimano BB MT501, press fit

HJUL	
FÄLGAR	27.5": Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width 29": Giant AM 29, tubeless ready, sleeve-joint rim, 30mm inner width
NAV	alloy
EKRAR	Sapim
DÄCK	27.5": [F] Maxxis Minion DHF 27.5x2.6, EXO, TR, tubeless [R] Maxxis Dissector 27.5x2.6, EXO, TR, tubeless 29": [F] Maxxis Minion DHF 29x2.5 WT, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4 WT, EXO, TR, tubeless
EXTRAFUNKTIONER	tubeless prepared, max tire size 2.6", max chainring size 32t

Price: 25 890,00 kr

## GEOMETRY

RAM	S (29")	M (29")	L (29")
Längd sadelrör (mm)	405	420	440
Seat Post Insertion Depth (mm)	220	235	255
Vinkel sadelrör	76,0°	76,0°	76,0°
Topprörets längd (mm)	565	585	605
Styrhuvud Längd (mm)	105	115	125
Vinkel styrhuvud	67,0°	67,0°	67,0°
Gaffelvinkel (mm)	51	51	51
Spår (mm)	105,3	105,3	105,3
Hjulbas (mm)	1147	1169	1190
Kedjestagslängd (mm)	438	438	438
Nedre fäste Drop (mm)	40	40	40
Stack (mm)	614	623	632
Reach (mm)	412	430	447
Stå över höjden (mm)	712	734	755
Styrets bredd (mm)	740	760	780
Stamlängd (mm)	40	50	50
Vevlängd (mm)	170	170	170
Hjulstorlek	29"	29"	29"

All specifications listed are subject to change without notice.