EMBOLDEN



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	27.5": XS, S , 29": S, M, L
FARBE	Pale Moss
RAHMEN	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface
GABEL	Giant STL 34 dual air, 140mm, 15x110, thru-axle
DÄMPFER	Crest FloTrac Elite TR, 2-position lockout, 210x52.5, custom tuned for Liv
KOMPONENTEN	
LENKER	Giant Contact TR35, 35mm XS:20mm rise / 760mm, S:20mm rise / 760mm, M:35mm rise / 760mm, L:35mm rise 800mm
GRIFFE	Tactal Pro, lock on XS & S: 120mm, M & L: 130mm
VORBAU	Giant Contact SL 35 XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SATTELSTÜTZE	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 140-170mm travel / 30.9 x 470mm
SATTEL	Liv Contact Ergo Trail
ANTRIEB	
SCHALTHEBEL	Shimano CUES SL-6000, 1x10
UMWERFER	N/A
SCHALTWERK	Shimano CUES RD-U6000, Shadow +
BREMSEN	Tektro HD-M5141, hydraulic, TR-54, 6-bolt rotors [F]180mm, [R]180mm
BREMSHEBEL	Tektro HD-M5141
KASSETTE	Shimano CUES, CS-LG300, 11x48
KETTE	KMC X-11
KURBEL	Shimano CUES FC-U6000, XS: 165mm, S: 165mm, M: 165mm, L: 165mm, 34T for 27.5", 32T for 29"
TRETLAGER	Shimano, threaded

LAUFRÄDER	
FELGEN	Giant AM30 alloy rim
NABE	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt, HG driver body
SPEICHEN	stainless, 28, J-bend
REIFEN	XS & S: [F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Minion DHR II 27.5x2.4, Dual, EXO, TR, tubeless M & L: [F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Minion DHR II 29x2.4, Dual, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.5", max chainring size 34t

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	380	390	420	450
Seat Post Insertion Depth (mm)	250	260	290	320
Sitzrohrwinkel	77.0°	77.0°	77.0°	77.0°
Oberrohrlänge (mm)	548	564	584	605
Steuerrohr-Länge (mm)	90	100	105	115
Steuerrohr-Winkel	65.0°	65.0°	65.0°	65.0°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	129	129	129	129
Radstand (mm)	1158	1176	1194	1217
Kettenstreben-Länge (mm)	440	440	442	442
Tretlager-Höhe (mm)	25	25	40	40
Stack (mm)	609	618	618	627
Reach (mm)	407	422	436	455
Überstandshöhe (mm)	758	757	750	745
Lenkerbreite (mm)	760	760	760	800
Vorbaulänge (mm)	40	50	50	50
Kurbellänge (mm)	165	165	165	165
Radgrösse	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.