

EMBOLDEN E+ 1



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 3X 100Nm, PedalPlus 6-Sensor technology
BEDIENINGSUNIT	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full color LCD display
ACCU	Giant EnergyPak 800Wh
LADER	Giant EnergyPak 4A smart charger
FRAME	
MATEN	XS, S, M, L
KLEUREN	Pale Moss
FRAME	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185X52.5mm shock, 1.5-1.8" headset (Z562/Z572)
VOORVORK	Giant STL 36 Air, 150mm travel, 5-position compression adjust, tapered steerer, 72mm crown, e-bike optimized, 110x15mm Boost axle, full fender compatible
DEMPER	Giant Crest FloTrac, 3-position lever, e-bike optimized, 185x52.5mm, Sag recommendation: 30% (15.75mm)
ONDERDELEN	
STUUR	Giant Connect TR35, 20mm rise, 35x750mm [XS, S], 35x780mm [M, L]
HANDVATTEN	Retrieving data. Wait a few seconds and try to cut or copy again.
STUURPEN	Retrieving data. Wait a few seconds and try to cut or copy again.
ZADEL PEN	Giant Contact Switch AT travel adjust dropper seatpost (XS, S: 110-140mm, M: 140-170mm, L: 170-200mm)
ZADEL	Liv Contact Ergo Trail
PEDALEN	Large platform pedal, 28-pins, PP cage, steel axle
AFMONTAGE	
SHIFTERS	Shimano Cues LinkGlide
ACHTERDERAILLEUR	Shimano Cues LinkGlide, 10-speed, Shadow+
REMMEN	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 220mm [F], 203mm [R]
REMHENDELS	Shimano Deore, BL-M401
CASSETTE	Shimano Cues LinkGlide, 10-speed, 11-48T
AANDRIJVING	Shimano LinkGlide
CRANKSET	Direct-mount steel 36T (maximum: 38T), Forged aluminum crank arms

WIELSET	
VELGEN	Giant AM30, tubeless ready, 30mm inner width
NAVEN	Shimano TC500 Boost, center-lock, 15x110mm [F], 12x148mm [R]
SPAKEN	Stainless steel
BANDEN	Maxxis Minion DHF 27x2.5" (XS), 29x2.50" (S, M, L) foldable, TLR EXO [F], Maxxis Dissector 27.5x2.4" (XS), 29x2.40" (S, M, L) foldable WT, TLR, EXO [R]
EXTRA'S	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
SLOT	Torx 25 battery lock with built-in torque limiter
SPATBORD/ KETTINGKAST	MRP 1x HD guide, CS e-Mount, 32-38T adjustable

Adviesprijs: € 4.499,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis hoek	77,5°	76,5°	76,5°	76,5°
Frame Lengte (horizontaal) (mm)	555	575	595	615
Balhoofdbuis Lengte (mm)	105	105	115	125
Balhoofdbuis Hoek	64,5°	64,5°	64,5°	64,5°
Wielbasis (mm)	1217	1226	1248	1270
Liggende achtervork lengte (mm)	468	468	468	468
Stack (mm)	619	619	628	637
Reach (mm)	417	426	444	462
Stand Over Height (mm)	689	710	726	736
Cranklengte (mm)	165	165	165	165

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.