

EMBOLDEN E+ 2 625



SPECS

HYBRID CYCLING TECHNOLOGY

MOTOR	SyncDrive Sport 2, 75Nm, powered by Yamaha
CONTROLLER	RideControl Dash
DISPLAY	RideControl Dash, full colour LCD screen
BATTERY	EnergyPak Smart 625, EnergyPak Plus 250Wh range extender compatible
MAXIMUM ASSISTED SPEED	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed

FRAME

SIZES	XS: 27.5" / S, M, L: 29"
COLOURS	Cosmos Navy
FRAME	ALUXX SL-Grade aluminium, 125mm travel FlexPoint suspension system, 12x148mm thru-axle, UDH hanger
FORK	SR Suntour XCR 34 LO-R, 140mm travel, tapered steerer, Lockout, 110x15 thru-axle
SHOCK	SR Suntour Raidon R, 190x45mm, custom tuned

COMPONENTS

HANDLEBAR	Giant Connect TR Riser
GRIPS	Liv Tactal Pro Single Lock-On Grips
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Liv sylvia E
PEDALS	Platform

DRIVETRAIN

SHIFTERS	Shimano Deore LinkGlide
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore LinkGlide, 10-speed
BRAKES	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Tektro HD-M745 Orion
CASSETTE	Shimano CS-LG400-10, 11-43T, 10-speed LinkGlide
CHAIN	Shimano, LinkGlide, CN-LG500
CRANKSET	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
BOTTOM BRACKET	N/A

WHEELS

RIMS	Giant AM 27.5" (XS), 29"(S, M, L)
HUBS	Giant eTracker Boost, [F] 110x15 [R] 148x12mm
SPOKES	Stainless Steel
TYRES	Maxxis Minion DHF 27x2.5"(XS), 29x2.50"(S, M, L) Foldable, TLR, EXO, 60TPI [F]Maxxis Dissector 27.5x2.4"(XS), 29x2.40"(S, M, L) Foldable WT, TLR, EXO, 60TPI [R]

EXTRAS

-

ACCESSORIES

LIGHTING	-
LOCK	Torx 25 Battery Lock with built-in Torque limiter
CARRIER	-

Price: \$6,299.00

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	380	395	425	455
Seat Tube Angle	77.0°	76.5°	76.0°	76.0°
Top Tube Length (mm)	565	575	595	615
Head Tube Length (mm)	105	105	115	125
Head Tube Angle	66.0°	66.0°	66.0°	66.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	121	121	121	121
Wheelbase (mm)	1201	1199	1215	1237
Chain Stay Length (mm)	468	468	468	468
Bottom Bracket Drop (mm)	20	40	40	40
Stack (mm)	601	621	630	639
Reach (mm)	426	425	437	455
Stand Over Height (mm)	690	710	735	760
Stem Length (mm)	40	40	50	60
Crank Length (mm)	165	165	165	165
Wheel Size	27.5"	29"	29"	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.