



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	SyncDrive Sport 2, 75Nm, powered by Yamaha
SENSOR	RideControl Dash
PRIKAZ	RideControl Dash, full color lcd screen
BATERIJA	EnergyPak Smart 500, EnergyPak Plus 250Wh range extender compatible
OKVIR	
VELIČINE	XS, S, M, L, (XS: 27.5" / S, M, L: 29")
BOJE	Cosmos Navy
OKVIR	ALUXX SL-grade aluminum, 125mm travel FlexPoint suspension system, 148x12 rear axle, Universal Derrailleur hanger, 184x44 shock, 1.5~1.8" headset
VILICA	SR Suntour XCR 34 LO-R, 140mm travel, tapered steerer, Lockout, 110x15 thru-axle
AMORTIZER	SR Suntour Raidon R, 190x45mm, custom tuned
KOMPONENTE	
VOLAN	Giant Connect TR Riser 31.8x750mm (XS-S), 780mm (M-L)
GRIPS	Liv Tactal Pro Single Lock-On Grips
LULA VOLANA	Giant Contact
CIJEV SJEDALA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SJEDALO	Liv sylvia E
PEDALE	Aluminum Platform
POGON	
RUČICE MJENJAČA	Shimano Deore LinkGlide
PREDNJI MJENJAČ	MRP HD2 co-moulded chain guide
STRAŽNJI MJENJAČ	Shimano Deore LinkGlide, 10-speed
KOČNICE	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
RUČICE KOČNICA	Tektro HD-M745 Orion
KAZETA	Shimano CS-LG400-10, 11-43T, 10-speed LinkGlide
LANAC	Shimano, LinkGlide, CN-LG500
POGON	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
OSOVINA POGONA (BB)	n/a

KOTAČI	
OBRUČI	AM30, 27.5" (XS), 29"(S, M, L), Tubeless ready, 30mm inner width
NABE	Giant eTracker Boost, [F] 110x15 [R] 148x12mm
ŽBICE	Stainless Steel
GUME	Maxxis Minion DHF 27x2.5"(XS), 29X2.50"(S, M, L) Foldable, TLR, EXO, 60TPI [F]Maxxis Dissector 27.5x2.4"(XS), 29X2.40"(S, M, L) Foldable WT, TLR, EXO, 60TPI [R]
DODACI	-
DODACI	
SVJETLA	-
LOKOTI	Torx 25 Battery Lock with built-in Torque limiter
NOSAČ	-

GEOMETRIJA

OKVIR	XS	S	M	L
Dužina cijevi sjedala (mm)	380	395	425	455
Kut cijevi sjedala	77,0°	76,5°	76,0°	76,0°
Dužina gornje cijevi (mm)	565	575	595	615
Dužina prednje cijevi (mm)	105	105	115	125
Kut vilice	66,0°	66,0°	66,0°	66,0°
Zakrivljenost vilice (offset) (mm)	44	44	44	44
Staza (mm)	121	121	121	121
Međuosovinski razmak kotača (mm)	1201	1199	1215	1237
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	468	468	468	468
Položaj osovine pogona (mm)	20	40	40	40
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	601	621	630	639
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	426	425	437	455
Prekoračna visina (mm)	690	710	735	760
Širina volana (mm)	750	750	780	780
Dužina lule volana (mm)	40	40	50	60
Dužina poluge pedale (mm)	165	165	165	165
Veličina kotača	27.5"	29"	29"	29"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.