



SPECS

HYBRID SYKKEL TEKNOLOGI	
MOTOR	SyncDrive Sport 2, 75Nm, powered by Yamaha
SENSOR	RideControl Dash
DISPLAY	RideControl Dash, full color lcd screen
BATTERI	EnergyPak Smart 500, EnergyPak Plus 250Wh range extender compatible
RAMME	
STØRRELSE	XS, S, M, L, (XS: 27.5" / S, M, L: 29")
FARGE	Cosmos Navy
RAMME	ALUXX SL-grade aluminum, 125mm travel FlexPoint suspension system, 148x12 rear axle, Universal Derrailleur hanger, 184x44 shock, 1.5~1.8" headset
GAFFEL	SR Suntour XCR 34 LO-R, 140mm travel, tapered steerer, Lockout, 110x15 thru-axle
DEMPER	SR Suntour Raidon R, 190x45mm, custom tuned
KOMPONENTER	
STYRE	Giant Connect TR Riser 31.8x750mm (XS-S), 780mm (M-L)
GRIPS	Liv Tactal Pro Single Lock-On Grips
STYRSTEM	Giant Contact
SETEPINNE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADEL	Liv sylvia E
PEDALER	Aluminum Platform
DRIVVERK	
GIRHENDLER	Shimano Deore LinkGlide
FRONTGIR	MRP HD2 co-moulded chain guide
BAKGIR	Shimano Deore LinkGlide, 10-speed
BREMSE	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
BREMSEHENDLER	Tektro HD-M745 Orion
KASSETT	Shimano CS-LG400-10, 11-43T, 10-speed LinkGlide
KJEDE	Shimano, LinkGlide, CN-LG500
KRANK	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
BOTTOM BRACKET	n/a

HJUL	
FELG	AM30, 27.5" (XS), 29"(S, M, L), Tubeless ready, 30mm inner width
NAV	Giant eTracker Boost, [F] 110x15 [R] 148x12mm
EIKE	Stainless Steel
DEKK	Maxxis Minion DHF 27x2.5"(XS), 29X2.50"(S, M, L) Foldable, TLR, EXO, 60TPI [F]Maxxis Dissector 27.5x2.4"(XS), 29X2.40"(S, M, L) Foldable WT, TLR, EXO, 60TPI [R]
EXTRAS	-
TILBEHØR	
LYS	-
LÅS	Torx 25 Battery Lock with built-in Torque limiter
BAGASJEBRETT	-

GEOMETRI

RAMME	XS	S	M	L
Seat Tube Length (mm)	380	395	425	455
Seat Tube Angle	77,0°	76,5°	76,0°	76,0°
Top Tube Length (mm)	565	575	595	615
Head Tube Length (mm)	105	105	115	125
Head Tube Angle	66,0°	66,0°	66,0°	66,0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	121	121	121	121
Wheelbase (mm)	1201	1199	1215	1237
Chain Stay Length (mm)	468	468	468	468
Bottom Bracket Drop (mm)	20	40	40	40
Stack (mm)	601	621	630	639
Reach (mm)	426	425	437	455
Stand Over Height (mm)	690	710	735	760
Handlebar Width (mm)	750	750	780	780
Stem Length (mm)	40	40	50	60
Crank Length (mm)	165	165	165	165
Wheel Size	27.5"	29"	29"	29"

Alle spesifikasjonene kan endres uten varsel.