



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Sport 2, 75Nm, powered by Yamaha
SENSOR	RideControl Dash
DISPLAY	RideControl Dash, full color lcd screen
BATTERY	EnergyPak Smart 500, EnergyPak Plus 250Wh range extender compatible
CADRU	
MARIMI	XS, S, M, L, (XS: 27.5" / S, M, L: 29")
CULORI	Cosmos Navy
CADRU	ALUXX SL-grade aluminum, 125mm travel FlexPoint suspension system, 148x12 rear axle, Universal Derrailleur hanger, 184x44 shock, 1.5~1.8" headset
FURCA	SR Suntour XCR 34 LO-R, 140mm travel, tapered steerer, Lockout, 110x15 thru-axle
SOC	SR Suntour Raidon R, 190x45mm, custom tuned
COMPONENTE	
GHIDON	Giant Connect TR Riser 31.8x750mm (XS-S), 780mm (M-L)
GRIPS	Liv Tactal Pro Single Lock-On Grips
PIPA	Giant Contact
TIJA SA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SA	Liv sylvia E
PEDALE	Aluminum Platform
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano Deore LinkGlide
SCHIMBATOR FATA	MRP HD2 co-moulded chain guide
SCHIMBATOR SPATE	Shimano Deore LinkGlide, 10-speed
FRANE	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
MANETE FRANA	Tektro HD-M745 Orion
PINIOANE	Shimano CS-LG400-10, 11-43T, 10-speed LinkGlide
LANT	Shimano, LinkGlide, CN-LG500
ANGRENAJ	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
BOTTOM BRACKET	n/a

ROTI	
JANTE	AM30, 27.5" (XS), 29"(S, M, L), Tubeless ready, 30mm inner width
BUTUCI	Giant eTracker Boost, [F] 110x15 [R] 148x12mm
SPITE	Stainless Steel
ANVELOPE	Maxxis Minion DHF 27x2.5"(XS), 29X2.50"(S, M, L) Foldable, TLR, EXO, 60TPI [F]Maxxis Dissector 27.5x2.4"(XS), 29X2.40"(S, M, L) Foldable WT, TLR, EXO, 60TPI [R]
EXTRAS	-
ACCESSORIES	
LIGHTING	-
LOCK	Torx 25 Battery Lock with built-in Torque limiter
CARRIER	-

GEOMETRIE

CADRU	XS	S	M	L
Seat Tube Length (mm)	380	395	425	455
Seat Tube Angle	77,0°	76,5°	76,0°	76,0°
Top Tube Length (mm)	565	575	595	615
Head Tube Length (mm)	105	105	115	125
Head Tube Angle	66,0°	66,0°	66,0°	66,0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	121	121	121	121
Wheelbase (mm)	1201	1199	1215	1237
Chain Stay Length (mm)	468	468	468	468
Bottom Bracket Drop (mm)	20	40	40	40
Stack (mm)	601	621	630	639
Reach (mm)	426	425	437	455
Stand Over Height (mm)	690	710	735	760
Handlebar Width (mm)	750	750	780	780
Stem Length (mm)	40	40	50	60
Crank Length (mm)	165	165	165	165
Wheel Size	27.5"	29"	29"	29"

Toate specificatiile enumerate se pot schimba fara notificare prealabila.