

EMBOLDEN E+ 2



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDrive Sport 2, 75Nm, powered by Yamaha
TIPALO	RideControl Dash
PRIKAZOVALNIK	RideControl Dash, full color lcd screen
BATERIJA	EnergyPak Smart 500, EnergyPak Plus 250Wh range extender compatible
OKVIR	
VELIKOSTI	XS, S, M, L, (XS: 27.5" / S, M, L: 29")
BARVE	Cosmos Navy
OKVIR	ALUXX SL-grade aluminum, 125mm travel FlexPoint suspension system, 148x12 rear axle, Universal Derrailleur hanger, 184x44 shock, 1.5~1.8" headset
VILICE	SR Suntour XCR 34 LO-R, 140mm travel, tapered steerer, Lockout, 110x15 thru-axle
AMORTIZER	SR Suntour Raidon R, 190x45mm, custom tuned
KOMPONENTE	
KRMILO	Giant Connect TR Riser 31.8x750mm (XS-S), 780mm (M-L)
GRIPS	Liv Tactal Pro Single Lock-On Grips
OPORA KRMILA	Giant Contact
OPORA SEDEŽA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SEDEŽ	Liv sylvia E
PEDALA	Aluminum Platform
POGON	
PRESTAVNE ROČICE	Shimano Deore LinkGlide
PREDNJI MENJALNIK	MRP HD2 co-moulded chain guide
ZADNJI MENJALNIK	Shimano Deore LinkGlide, 10-speed
ZAVORE	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
ZAVORNE ROČICE	Tektro HD-M745 Orion
VERIŽNIK	Shimano CS-LG400-10, 11-43T, 10-speed LinkGlide
VERIGA	Shimano, LinkGlide, CN-LG500
GONILKE Z VERIŽNIKI	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
BOTTOM BRACKET	n/a

OBROČNIKI	
OBROČI	AM30, 27.5" (XS), 29"(S, M, L), Tubeless ready, 30mm inner width
PESTA	Giant eTracker Boost, [F] 110x15 [R] 148x12mm
NAPERE	Stainless Steel
PLAŠČI	Maxxis Minion DHF 27x2.5"(XS), 29X2.50"(S, M, L) Foldable, TLR, EXO, 60TPI [F]Maxxis Dissector 27.5x2.4"(XS), 29X2.40"(S, M, L) Foldable WT, TLR, EXO, 60TPI [R]
DODATKI	-
DODATNA OPREMA	
SVETILA	-
KLJUČAVNICA	Torx 25 Battery Lock with built-in Torque limiter
PRTLJAŽNIK	-

GEOMETRIJA

OKVIR	XS	S	M	L
Dolžina sedežne cevi (mm)	380	395	425	455
Kot sedežne cevi	77,0°	76,5°	76,0°	76,0°
Top Tube Length (mm)	565	575	595	615
Višina glave okvirja (mm)	105	105	115	125
Krmilni kot	66,0°	66,0°	66,0°	66,0°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	121	121	121	121
Medosna razdalja (mm)	1201	1199	1215	1237
Dolžina cevi ob verigi (mm)	468	468	468	468
Bottom Bracket Drop (mm)	20	40	40	40
Oddaljenost zgornje cevi od gonilne osi (mm)	601	621	630	639
Doseg (mm)	426	425	437	455
Višina zgornje cevi (mm)	690	710	735	760
Širina krmila (mm)	750	750	780	780
Dolžina opore krmila (mm)	40	40	50	60
Dolžina gonilke (mm)	165	165	165	165
Velikost obročnikov	27.5"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.