EMBOLDEN

SPECS

FRAME	
SIZES	XS, S: (F 29"/R 27.5"), M: (F/R 29")
COLOURS	Pale Moss
FRAME	ALUXX-Grade aluminium, UDH, 130mm FlexPoint suspension, 12x148mm thru-axle
FORK	Giant STL 34 dual air, 140mm travel, Boost 15x110
SHOCK	Crest, FloTrac Elite TR, 2 position lever
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 35mm
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL35 XS: 40 S:40mm, M:40mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm
SADDLE	ErgoContact Trail
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano CUES SL-6000, 1x10
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano CUES, U6000, Shadow+
BRAKES	Tektro Gemini M535, 4 piston, hydraulic, TRP rotors 180mm
BRAKE LEVERS	Tektro Gemini M535
CASSETTE	Shimano CUES, LG300, 11-48
CHAIN	KMC X-11
CRANKSET	Shimano CUES, U6000-1, 30t XS:165mm, S:165mm, M:165mm
BOTTOM BRACKET	Shimano, threaded

WHEELS	
RIMS	Giant AM30 tubeless ready sleeve-joint rim 29"F/27.5"R for frame sizes XS/S, 29"F&R for frame sizes for M
HUBS	[F] Giant Boost 110x15, Sealed Bearing [R] Giant Boost 148x12, Sealed Bearing, HG
SPOKES	Sapim Race
TYRES	[F] Maxxis Dissector 29x2.4WT, TLR, EXO, Tubeless [R, size M] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, or [R, size XS and S] Maxxis Dissector 27.5x2.4WT, TLR, EXO, tubeless
EXTRAS	Tubeless prepared, max tyre size 2.5", max chainring size 32t for 29", 34t for 27.5"
LIMITS	
MAX TYRE CLEARANCE	2.5"
MAX CHAINRING SIZE	32t for 29", 34t for 27.5"

Price: $3,299.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	380	390	420
Seat Post Insertion Depth (mm)	250	260	290
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (mm)	548	564	584
Head Tube Length (mm)	90	100	105
Head Tube Angle	65.0°	65.0°	65.0°
Fork Rake (mm)	44	44	44
Trail (mm)	129	129	129
Wheelbase (mm)	1158	1176	1194
Chain Stay Length (mm)	440	440	442
Bottom Bracket Drop (mm)	25	25	40
Stack (mm)	609	618	618
Reach (mm)	407	422	436
Stand Over Height (mm)	758	757	750
Stem Length (mm)	40	50	50
Crank Length (mm)	165	165	165
Wheel Size	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29"

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.*