



## SPECS

FRAME	
<b>SIZES</b>	27.5": XS, S, 29": S, M, L
<b>COLOURS</b>	Pale Moss
<b>FRAME</b>	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface
<b>FORK</b>	Giant STL 34 dual air, 140mm, 15x110, thru-axle
<b>SHOCK</b>	Crest FloTrac Elite TR, 2-position lockout, 210x52.5, custom tuned for Liv
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact TR35, 35mm XS:20mm rise / 760mm, S:20mm rise / 760mm, M:35mm rise / 760mm, L:35mm rise 800mm
<b>GRIPS</b>	Tactal Pro, lock on XS & S: 120mm, M & L: 130mm
<b>STEM</b>	Giant Contact SL 35 XS: 40mm, S: 50mm, M: 50mm, L: 50mm
<b>SEATPOST</b>	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 140-170mm travel / 30.9 x 470mm
<b>SADDLE</b>	Liv Contact Ergo Trail
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano CUES SL-6000, 1x10
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	Shimano CUES RD-U6000, Shadow +
<b>BRAKES</b>	Tektro HD-M5141, hydraulic, TR-54, 6-bolt rotors [F]180mm, [R]180mm
<b>BRAKE LEVERS</b>	Tektro HD-M5141
<b>CASSETTE</b>	Shimano CUES, CS-LG300, 11x48
<b>CHAIN</b>	KMC X-11
<b>CRANKSET</b>	Shimano CUES FC-U6000, XS: 165mm, S: 165mm, M: 165mm, L: 165mm, 34T for 27.5", 32T for 29"
<b>BOTTOM BRACKET</b>	Shimano, threaded

WHEELS	
<b>RIMS</b>	Giant AM30 alloy rim
<b>HUBS</b>	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt, HG driver body
<b>SPOKES</b>	stainless, 28, J-bend
<b>TYRES</b>	XS & S: [F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Minion DHR II 27.5x2.4, Dual, EXO, TR, tubeless M & L: [F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Minion DHR II 29x2.4, Dual, EXO, TR, tubeless
<b>EXTRAS</b>	tubeless prepared, max tire size 2.5", max chaining size 34t

**Price: £1,999.00**

## GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	380	390	420	450
Seat Post Insertion Depth (mm)	250	260	290	320
Seat Tube Angle	77.0°	77.0°	77.0°	77.0°
Top Tube Length (mm)	548	564	584	605
Head Tube Length (mm)	90	100	105	115
Head Tube Angle	65.0°	65.0°	65.0°	65.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	129	129	129	129
Wheelbase (mm)	1158	1176	1194	1217
Chain Stay Length (mm)	440	440	442	442
Bottom Bracket Drop (mm)	25	25	40	40
Stack (mm)	609	618	618	627
Reach (mm)	407	422	436	455
Stand Over Height (mm)	758	757	750	745
Handlebar Width (mm)	760	760	760	800
Stem Length (mm)	40	50	50	50
Crank Length (mm)	165	165	165	165
Wheel Size	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29"	29"

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.