



ESPECIFICACIONES

CUADRO	
TALLAS	27.5": XS, S , 29": S, M, L
COLORES	Black Diamond, Sangria
CUADRO	ALUXX-grade aluminum, 120mm FlexPoint Suspension, 12x148mm thru-axle
TIJERA	Giant STL 34 RCL, 140mm, Boost 15x110 QR
AMORTIGUADOR	Suntour Raidon R, 184x44mm, recommended sag 30%
COMPONENTES	
MANUBRIO	Giant Contact TR35, 760x35mm, 20mm rise, alloy
GRIPS	Liv Sole-O
POTENCIA	Giant Contact SL 35 27.5": XS: 40mm, S: 50mm 29": S: 50mm, M: 50mm, L: 60mm
POSTE DE ASIENTO	Giant Contact Switch AT dropper, remote 27.5": XS: 70-100mm travel / 30.9 x 315mmS: 70-100mm travel / 30.9 x 315mm29":S: 70-100mm travel / 30.9 x 315mmM: 110-140mm travel / 30.9 x 395mmL: 110-140mm travel / 30.9 x 395mm
ASIENTO	Liv Sylvia
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Cues SL-6000, 1x10
DESVIADOR	N/A
CAMBIO TRASERO	Shimano CuesRD-U6000, Shadow+
FRENOS	Shimano BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
PALANCAS DE FRENOS	Shimano MT-401
CASSETTE	Shimano CUES, CS-LG300, 11x48
CADENA	KMC X-11
MULTIPLICACIÓN	Shimano CUES FC-U6000, 30t27.5": XS: 165mm, S: 170mmPraxis Cadet 30t29": S: 170mm, M: 170mm, L: 170mm
EJE DE CENTRO	27.5" Shimano, threaded29" Praxis threaded

RUEDAS	
RUEDAS	27.5" and 29": Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
MAZAS	27.5" and 29": [F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, HG driver body
RAYOS	Sapim, 28, J-bend
NEUMÁTICOS	27.5": [F] Maxxis Minion DHF 27.5x2.6, EXO, TR [R] Maxxis Dissector 27.5x2.6, Dual, EXO, TR, tubeless 29": [F] Maxxis Minion DHF 29x2.5 WT, EXO, TR [R] Maxxis Dissector 29x2.4 WT, Dual, EXO, TR, tubeless
EXTRAS	27.5" and 29": tubeless prepared, max tire size 2.6", max chainring size 32t

Precio: \$52,990.00

GEOMETRÍA

CUADRO	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")
Longitud de la Base del Poste de Asiento (mm)	380	406	405	420	440
Seat Post Insertion Depth (mm)	145	170	220	235	255
Ángulo de la Base del Poste de Asiento	74.0°	74.0°	76.0°	76.0°	76.0°
Longitud del Tubo Superior (mm)	565	580	565	585	605
Longitud del Telescopio (mm)	95	100	105	115	125
Ángulo del Telescopio	67.5°	67.5°	67.0°	67.0°	67.0°
Rake (mm)	43	43	51	51	51
Trail (mm)	103.6	103.6	105.3	105.3	105.3
Distancia entre Ejes (mm)	1109	1125	1147	1169	1190
Longitud de Vaina Inferior (mm)	435	435	438	438	438
Caída del Eje de Centro (mm)	20	20	40	40	40
Stack (mm)	560	565	614	623	632
Reach (mm)	404	418	412	430	447
Altura del Tubo Superior al Suelo (mm)	690	705	712	734	755
Ancho del Manubrio (mm)	750	750	740	760	780
Longitud de la Potencia (mm)	40	40	40	50	50
Longitud de la Biela (mm)	165	170	170	170	170
Tamaño de las Ruedas	27.5"	27.5"	29"	29"	29"

Todas las especificaciones están sujetas a cambios sin previo aviso.