



ESPECIFICACIONES

CUADRO	
TALLAS	27.5": XS, S , 29": S, M, L
COLORES	Pale Moss, Red Clay
CUADRO	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface
TIJERA	Giant STL 34 dual air, 140mm, 15x110, thru-axle
AMORTIGUADOR	Giant U.S.: Fox Rhythm, rebound, 210x52.5, custom tuned for Liv Other GSCs: Crest FloTrac Elite TR, 2-position lockout, 210x52.5, custom tuned for Liv
COMPONENTES	
MANUBRIO	Giant Contact TR35, 35mm XS:20mm rise / 760mm, S:20mm rise / 760mm, M:35mm rise / 760mm, L:35mm rise 800mm
GRIPS	Tactal Pro, lock on XS & S: 120mm, M & L: 130mm
POTENCIA	Giant Contact SL 35 XS: 40mm, S: 50mm, M: 50mm, L: 50mm
POSTE DE ASIENTO	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 140-170mm travel / 30.9 x 470mm
ASIENTO	Liv Contact Ergo Trail
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano CUES SL-6000, 1x10
DESVIADOR	N/A
CAMBIO TRASERO	Shimano CUES RD-U6000, Shadow +
FRENOS	Tektro HD-M5141, hydraulic, TR-54, 6-bolt rotors [F]180mm, [R]180mm
PALANCAS DE FRENOS	Tektro HD-M5141
CASSETTE	Shimano CUES, CS-LG300, 11x48
CADENA	KMC X-11
MULTIPLICACIÓN	Shimano CUES FC-U6000, XS: 165mm, S: 165mm, M: 165mm, L: 165mm, 34T for 27.5", 32T for 29"
EJE DE CENTRO	Shimano, threaded

RUEDAS	
RUEDAS	Giant AM30 alloy rim
MAZAS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt, HG driver body
RAYOS	stainless, 28, J-bend
NEUMÁTICOS	XS & S: [F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Minion DHR II 27.5x2.4, Dual, EXO, TR, tubeless M & L: [F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Minion DHR II 29x2.4, Dual, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.5", max chainring size 34t

Precio: \$54,990.00

GEOMETRÍA

CUADRO	XS	S	M
Longitud de la Base del Poste de Asiento (mm)	380	390	420
Seat Post Insertion Depth (mm)	250	260	290
Ángulo de la Base del Poste de Asiento	77.0°	77.0°	77.0°
Longitud del Tubo Superior (mm)	548	564	584
Longitud del Telescopio (mm)	90	100	105
Ángulo del Telescopio	65.0°	65.0°	65.0°
Rake (mm)	44	44	44
Trail (mm)	129	129	129
Distancia entre Ejes (mm)	1158	1176	1194
Longitud de Vaina Inferior (mm)	440	440	442
Caída del Eje de Centro (mm)	25	25	40
Stack (mm)	609	618	618
Reach (mm)	407	422	436
Altura del Tubo Superior al Suelo (mm)	758	757	750
Ancho del Manubrio (mm)	760	760	760
Longitud de la Potencia (mm)	40	50	50
Longitud de la Biela (mm)	165	165	165
Tamaño de las Ruedas	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29"

Todas las especificaciones están sujetas a cambios sin previo aviso.