

EMBOLDEN



SPECS

FRAME	
SIZES	27.5": XS, S, 29": S, M, L
COLORS	Pale Moss, Red Clay
FRAME	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface
FORK	Giant STL 34 dual air, 140mm, 15x110, thru-axle
SHOCK	Giant U.S.: Fox Rhythm, rebound, 210x52.5, custom tuned for Liv Other GSCs: Crest FloTrac Elite TR, 2-position lockout, 210x52.5, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 35mm XS:20mm rise / 760mm, S:20mm rise / 760mm, M:35mm rise / 760mm, L:35mm rise 800mm
GRIPS	Tactal Pro, lock on XS & S: 120mm, M & L: 130mm
STEM	Giant Contact SL 35 XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEATPOST	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 140-170mm travel / 30.9 x 470mm
SADDLE	Liv Contact Ergo Trail
DRIVETRAIN	
SHIFTERS	Shimano CUES SL-6000, 1x10
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano CUES RD-U6000, Shadow +
BRAKES	Tektro HD-M5141, hydraulic, TR-54, 6-bolt rotors [F]180mm, [R]180mm
BRAKE LEVERS	Tektro HD-M5141
CASSETTE	Shimano CUES, CS-LG300, 11x48
CHAIN	KMC X-11
CRANKSET	Shimano CUES FC-U6000, XS: 165mm, S: 165mm, M: 165mm, L: 165mm, 34T for 27.5", 32T for 29"
BOTTOM BRACKET	Shimano, threaded

WHEELS	
RIMS	Giant AM30 alloy rim
HUBS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt, HG driver body
SPOKES	stainless, 28, J-bend
TIRES	XS & S: [F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Minion DHR II 27.5x2.4, Dual, EXO, TR, tubeless M & L: [F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Minion DHR II 29x2.4, Dual, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.5", max chainring size 34t

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	380	390	420	450
Seat Post Insertion Depth (mm)	250	260	290	320
Seat Tube Angle	77,0°	77,0°	77,0°	77,0°
Top Tube Length (mm)	548	564	584	605
Head Tube Length (mm)	90	100	105	115
Head Tube Angle	65,0°	65,0°	65,0°	65,0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	129	129	129	129
Wheelbase (mm)	1158	1176	1194	1217
Chain Stay Length (mm)	440	440	442	442
Bottom Bracket Drop (mm)	25	25	40	40
Stack (mm)	609	618	618	627
Reach (mm)	407	422	436	455
Stand Over Height (mm)	758	757	750	745
Handlebar Width (mm)	760	760	760	800
Stem Length (mm)	40	50	50	50
Crank Length (mm)	165	165	165	165
Wheel Size	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29"	29"

All specifications listed are subject to change without notice.