ENVILIV ADVANCED 1



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Null White
FRAME	Advanced-grade Composite, 12x142mm thru-axle, UDH compatible, integrated seatpost, disc
FORK	Advanced -grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact SL Aero XS:36/38cm, S:36/38cm, M:37/40cm
GRIPS	Liv Stratus Lite 2.0
STEM	Liv Contact SL Aero XS:80mm, S:90mm, M:100mm
SEATPOST	Giant Vector, composite, -5/+15mm offset
SADDLE	Liv Alacra SL
DRIVETRAIN	
SHIFTERS	Shimano 105 Di2 ST-R7170
FRONT DERAILLEUR	Shimano 105 Di2 FD-R7150
REAR DERAILLEUR	Shimano 105 Di2 RD-R7150
BRAKES	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano 105 Di2 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x36
CHAIN	KMC X12
CRANKSET	Shimano 105, 36/52 XS:165mm, S:165mm, M:170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 2 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
HUBS	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant alloy, pawl driver (3-pawl 30T), CenterLock, 12mm thru-axle
SPOKES	Sapim Sprint
TYRES	Giant Gavia Course 0, tubeless, 700x28c (28mm), folding
EXTRAS	Water bottle cages, tubeless prepared, 32mm max tyre size
LIMITS	
MAX TYRE CLEARANCE	32mm

Price: $5,999.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	465	498	528
Seat Tube Angle	75.0°	74.5°	74.0°
Top Tube Length (mm)	514.8	526.2	541.2
Head Tube Length (mm)	115	130	150
Head Tube Angle	71.0°	72.0°	72.5°
Fork Rake (mm)	49	49	49
Trail (mm)	66.8	60.4	57.2
Wheelbase (mm)	974.7	977	984.1
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	72	70	70
Stack (mm)	511.8	527	547.8
Reach (mm)	372.9	377.8	382.9
Stand Over Height (mm)	732.6	760.8	786.9
Stem Length (mm)	80	90	100
Crank Length (mm)	165	165	170

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.*