

ENVILIV ADVANCED 1



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLOURS	Thundercloud/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive Aero steerer, 12x100mm, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Contact SL Aero, 31.8mm, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact SL Aero, XXS:80mm, XS:80mm, S:90mm, M:100mm, L:110mm
SEATPOST	Giant Vector, composite, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADDLE	Liv Alacra SL
DRIVETRAIN	
SHIFTERS	Shimano 105 Di2
FRONT DERAILLEUR	Shimano 105 Di2 FD-R7150
REAR DERAILLEUR	Shimano 105 Di2 RD-R7150
BRAKES	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors, [F] 160mm, [R] 140mm
BRAKE LEVERS	Shimano 105 Di2
CASSETTE	Shimano 105, 12-speed, 11x34
CHAIN	KMC X12L-1
CRANKSET	Shimano 105, 36/52, XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 2 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
HUBS	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, pawl driver(3-pawl 30T), CenterLock, 12mm thru-axle
SPOKES	SAPIM Sprint
TIRES	Giant Gavia Course 0, 700x28c, folding, tubeless
EXTRAS	computer mount, two bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

Suggested Retail Price (CDN): \$5,699.00

FRAME GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	470	500	530
Seat Tube Angle	75.0°	74.5°	74.0°
Top Tube Length (mm)	508	524	540
Head Tube Length (mm)	120	135	155
Head Tube Angle	71.0°	72.0°	72.5°
Fork Rake (mm)	49	49	49
Trail (mm)	66.3	59.9	56.8
Wheelbase (mm)	973	977	984
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	72	70	70
Stack (mm)	517	532	553
Reach (mm)	370	377	382
Stand Over Height (mm)	732	761	787
Handlebar Width (mm)	360	380	400
Stem Length (mm)	80	90	100
Crank Length (mm)	165	170	170

All prices and specifications are subject to change without notice.