

ENVILIV ADVANCED 1



ESPECIFICACIONES

CUADRO	
TALLAS	XXS, XS, S, M, L
COLORES	Null White, Neo-Gold
CUADRO	Advanced-grade composite, 12x142mm thru-axle, disc
HORQUILLA	Advanced-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
MANILLAR	Liv Contact SL Aero, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
PUÑOS	Liv Stratus Lite 2.0
POTENCIA	Liv Contact SL Aero, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
TIJA DE SILLÍN	Giant Vector, composite, -5/ +15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SILLÍN	Liv Alacra SL
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano 105 Di2
DESVIADOR	Shimano 105 Di2
CAMBIO TRASERO	Shimano 105 Di2
FRENOS	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F] 160mm, [R] 140mm
PALANCAS DE FRENOS	Shimano 105 Di2 hydraulic
CASETTE	Shimano 105, 12-speed, 11x36
CADENA	KMC X12L-1
JGO. PLATOS Y BIELAS	Shimano 105, 36/52 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
CAJA DE PEDALIER	Shimano, press fit

RUEDAS	
LLANTAS	Giant SLR 2 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
BUJES	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant alloy, pawl driver (3-pawl 30T), CenterLock, 12mm thru-axle
RADIOS	Sapim JB Sprint
CUBIERTAS	Giant Gavia Course, 700x28c, folding, tubeless
EXTRAS	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

Precio: 4.199,00 €

GEOMETRÍA

CUADRO	XXS	XS	S	M
Longitud del tubo del sillín (mm)	446,5	465	498	528
Ángulo del tubo del sillín	75,0°	75,0°	74,5°	74,0°
Longitud del tubo superior (mm) (mm)	504	514,8	526,2	541,2
Longitud del tubo de dirección (mm) (mm)	100	115	130	150
Ángulo del tubo de dirección	70,0°	71,0°	72,0°	72,5°
Inclinación de la horquilla (mm)	49	49	49	49
Trail (mm) (mm)	73,2	66,8	60,4	57,2
Distancia entre ejes (mm) (mm)	969,9	974,7	977	984,1
Longitud de la vaina (mm) (mm)	405	405	405	405
Caída del eje de pedalier (mm) (mm)	72	72	70	70
Stack (mm) (mm)	494,1	511,8	527	547,8
Reach (mm) (mm)	365,6	372,9	377,8	382,9
Altura del suelo al tubo (mm) (mm)	714,8	732,6	760,8	786,9
Ancho del manillar (mm) (mm)	360	380	380	400
Longitud de la potencia (mm) (mm)	80	80	90	100
Longitud de las bielas (mm) (mm)	160	165	165	170

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.