

ENVILIV ADVANCED 1



ESPECIFICACIONES

CUADRO	
TALLAS	XXS, XS, S, M, L
COLORES	Airglow
CUADRO	Advanced-Grade Composite, 12x142mm thru-axle, Disc
TIJERA	Advanced-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm, Disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Liv Contact SL Aero, 31.8mm XXS: 36cm, XS: 36cm, S: 38cm, M: 40cm, L: 42cm
GRIPS	Liv All Condition
POTENCIA	Giant Contact SL Aero XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
POSTE DE ASIENTO	Giant Vector, composite XXS:350mm, XS:350mm, S:350mm, M:350mm, L:350mm
ASIENTO	Liv Approach
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM Rival eTap AXS
DESVIADOR	SRAM Rival eTap AXS
CAMBIO TRASERO	SRAM Rival eTap AXS
FRENOS	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	SRAM Rival hydraulic
CASSETTE	SRAM Rival, 12-speed, 10x30
CADENA	SRAM Rival D1
MULTIPLICACIÓN	SRAM Rival D1 DUB, 35/48 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant SLR 2 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
MAZAS	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant alloy, pawl driver(3-pawl 30t), CenterLock, 12mm thru-axle
RAYOS	SAPIM Sprint
NEUMÁTICOS	Giant Gavia Course 1, 700x25c (28mm), folding, tubeless
EXTRAS	computer mount, two bottle cages, tubeless prepared, 30mm max tire size

Precio: \$84,990.00

GEOMETRÍA

CUADRO	XXS	XS	S	M	L
Longitud de la Base del Poste de Asiento (mm)	440	470	500	530	560
Ángulo de la Base del Poste de Asiento	75.0°	75.0°	74.5°	74.0°	73.5°
Longitud del Tubo Superior (mm)	498	508	524	540	555
Longitud del Telescopio (mm)	105	120	135	155	175
Ángulo del Telescopio	70.0°	71.0°	72.0°	72.5°	72.5°
Rake (mm)	49	49	49	49	49
Trail (mm)	73	66	60	57	57
Distancia entre Ejes (mm)	970	973	977	984	996
Longitud de Vaina Inferior (mm)	405	405	405	405	405
Caída del Eje de Centro (mm)	72	72	70	70	67
Stack (mm)	499	517	532	553	569
Reach (mm)	364	370	377	382	386
Altura del Tubo Superior al Suelo (mm)	706.1	731.8	761.1	787.4	815.3
Ancho del Manubrio (mm)	360	360	380	400	420
Longitud de la Potencia (mm)	80	80	90	100	110
Longitud de la Biela (mm)	165	165	170	170	172.5
Tamaño de las Ruedas	700C	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.