

ENVILIV ADVANCED 1



TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, L
VÄRIT	Null White
RUNKO	Advanced-grade composite, 12x142mm thru-axle, disc
HAARUKKA	Advanced-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMONENTIT	
OHJAUSTANKO	Liv Contact SL Aero, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
GRIPIT	Liv Stratus Lite 2.0
OHJAINKANNATIN	Liv Contact SL Aero, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SATULATOLPPA	Giant Vector, composite, -5/ +15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SATULA	Liv Alacra SL
VOIMANSIIRTO	
VAIHDEVIPU	Shimano 105 Di2
ETUVAIHTAJA	Shimano 105 Di2
TAKAVAIHTAJA	Shimano 105 Di2
JARRUT	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F] 160mm, [R] 140mm
JARRUKAHVAT	Shimano 105 Di2 hydraulic
RATASPAKKA	Shimano 105, 12-speed, 11x36
KETJUT	KMC X12L-1
KAMPISARJA	Shimano 105, 36/52 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
KESKIÖ	Shimano, press fit

RENKAAT	
VANTEET	Giant SLR 2 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
NAVAT	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant alloy, pawl driver (3-pawl 30T), CenterLock, 12mm thru-axle
PINNAT	Sapim JB Sprint
RENKAAT	Giant Gavia Course, 700x28c, folding, tubeless
LISÄTIEDOT	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

Suositusinta: 4 699,00 €

GEOMETRIA

RUNKO	XS	S	M	L
Satulaputken pituus (mm)	465	498	528	558
Satulaputken kulma	75,0°	74,5°	74,0°	73,5°
Vaakaputken pituus (mm)	514,8	526,2	541,2	560,6
Emäputken pituus (mm)	115	130	150	170
Emäputken kulma	71,0°	72,0°	72,5°	72,5°
Haarukan offset (mm)	49	49	49	49
Trail-mitta (mm)	66,8	60,4	57,2	57,2
Akseliväli (mm)	974,7	977	984,1	999,3
Takahaarukan alaputken pituus (mm)	405	405	405	405
Keskiön pudotus (mm)	72	70	70	70
Stack-mitta (mm)	511,8	527	547,8	566,9
Reach-mitta (mm)	372,9	377,8	382,9	392,1
Standover-mitta (mm)	732,6	760,8	786,9	814
Ohjaustangon leveys (mm)	380	380	400	420
Ohjainkannattimen pituus (mm)	80	90	100	110
Kammen pituus (mm)	165	165	170	170

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.