

ENVILIV ADVANCED 1



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XXS, XS, S, M, L
FARBE	Null White, Neo-Gold
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, disc
GABEL	Advanced-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTEN	
LENKER	Liv Contact SL Aero, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
GRIFFE	Liv Stratus Lite 2.0
VORBAU	Liv Contact SL Aero, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SATTELSTÜTZE	Giant Vector, composite, -5/ +15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SATTEL	Liv Alacra SL
ANTRIEB	
SCHALTHEBEL	Shimano 105 Di2
UMWERFER	Shimano 105 Di2
SCHALTWERK	Shimano 105 Di2
BREMSEN	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F] 160mm, [R] 140mm
BREMSHEBEL	Shimano 105 Di2 hydraulic
KASSETTE	Shimano 105, 12-speed, 11x36
KETTE	KMC X12L-1
KURBEL	Shimano 105, 36/52 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant SLR 2 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
NABE	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant alloy, pawl driver (3-pawl 30T), CenterLock, 12mm thru-axle
SPEICHEN	Sapim JB Sprint
REIFEN	Giant Gavia Course, 700x28c, folding, tubeless
EXTRAS	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

GEOMETRIEDATEN

RAHMEN	XXS	XS	S	M	L
Sitzrohrlänge (mm)	446.5	465	498	528	558
Sitzrohrwinkel	75.0°	75.0°	74.5°	74.0°	73.5°
Oberrohrlänge (mm)	504	514.8	526.2	541.2	560.6
Steuerrohr-Länge (mm)	100	115	130	150	170
Steuerrohr-Winkel	70.0°	71.0°	72.0°	72.5°	72.5°
Gabelneigung (mm)	49	49	49	49	49
Trail (mm)	73.2	66.8	60.4	57.2	57.2
Radstand (mm)	969.9	974.7	977	984.1	999.3
Kettenstreben-Länge (mm)	405	405	405	405	405
Tretlager-Höhe (mm)	72	72	70	70	70
Stack (mm)	494.1	511.8	527	547.8	566.9
Reach (mm)	365.6	372.9	377.8	382.9	392.1
Überstandshöhe (mm)	714.8	732.6	760.8	786.9	814
Lenkerbreite (mm)	360	380	380	400	420
Vorbaulänge (mm)	80	80	90	100	110
Kurbellänge (mm)	160	165	165	170	170

Spezifikations-, Preis- und Farbänderungen vorbehalten.