ENVILIV ADVANCED 2



ESPECIFICACIONES

CUADRO	
TALLAS	XXS, XS, S, M, L
COLORES	Sangria
CUADRO	Advanced-grade composite, 12x142mm thru-axle, disc
TIJERA	Advanced-grade composite, full-composite OverDrive 2 steerer, 12x100mm, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Liv Contact SL Aero, 31.8mm XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv All Condition
POTENCIA	Giant Contact SL Aero XXS:80mm, XS:80mm, S:90mm, M:100mm, L:110mm
POSTE DE ASIENTO	Giant Vector, composite XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
ASIENTO	Liv Approach
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano 105
DESVIADOR	Shimano 105
CAMBIO TRASERO	Shimano 105
FRENOS	Shimano 105 hydraulic, Shimano rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	Shimano 105 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x30
CADENA	KMC X11SL-1
MULTIPLICACIÓN	Shimano 105, 36/52 XXS:165mm, XS:165mm, S:170mm, M:170mm, L:172.5mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	Giant P-A2 Disc, alloy
MAZAS	Giant P-A2 Disc, 12mm thru-axle
RAYOS	Sapim
NEUMÁTICOS	Giant Gavia Course 1, 700x25c (28mm), folding, tubeless
EXTRAS	computer mount, two bottle cages, tubeless prepared, 30mm max tire size

Precio: $65,990.00

GEOMETRÍA

CUADRO	XXS	XS	S	M
Longitud de la Base del Poste de Asiento (mm)	440	470	500	530
Ángulo de la Base del Poste de Asiento	75.0°	75.0°	74.5°	74.0°
Longitud del Tubo Superior (mm)	498	508	524	540
Longitud del Telescopio (mm)	105	120	135	155
Ángulo del Telescopio	70.0°	71.0°	72.0°	72.5°
Rake (mm)	49	49	49	49
Trail (mm)	72.7	66.3	59.9	56.8
Distancia entre Ejes (mm)	970	973	977	984
Longitud de Vaina Inferior (mm)	405	405	405	405
Caída del Eje de Centro (mm)	72	72	70	70
Stack (mm)	499	517	532	553
Reach (mm)	364	370	377	382
Altura del Tubo Superior al Suelo (mm)	706.1	731.8	761.1	787.4
Ancho del Manubrio (mm)	360	360	380	400
Longitud de la Potencia (mm)	80	80	90	100
Longitud de la Biela (mm)	165	165	170	170
Tamaño de las Ruedas	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.