ENVILIV ADVANCED 2



ESPECIFICACIONES

CUADRO	
TALLAS	XXS, XS, S, M, L
COLORES	Midnight Pine, Desert Pearl
CUADRO	Advanced-grade composite, 12x142mm thru-axle, disc
TIJERA	Advanced-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
MANUBRIO	Liv Contact SL Aero, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
GRIPS	Liv Stratus Lite 2.0
POTENCIA	Liv Contact SL Aero, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
POSTE DE ASIENTO	Giant Vector, composite, -5/ +15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
ASIENTO	Liv Alacra SL
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano 105
DESVIADOR	Shimano 105
CAMBIO TRASERO	Shimano 105
FRENOS	Shimano 105 hydraulic, Shimano SM-RT64 [F]160mm, [R]140mm
PALANCAS DE FRENOS	Shimano 105 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x36
CADENA	KMC X12L-1
MULTIPLICACIÓN	Shimano 105, 36/52 XXS:160mm, XS:165mm, S:165mm, M:170mm, L:17omm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	Giant P-A1 Disc, alloy
MAZAS	Giant P-A1 Disc, 12mm thru-axle
RAYOS	stainless
NEUMÁTICOS	Giant Gavia Course, 700x28c, folding, tubeless
EXTRAS	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

Precio: $78,990.00

GEOMETRÍA

CUADRO	XXS	XS	S	M	L
Longitud de la Base del Poste de Asiento (mm)	446.5	465	498	528	558
Ángulo de la Base del Poste de Asiento	75.0°	75.0°	74.5°	74.0°	73.5°
Longitud del Tubo Superior (mm)	504	514.8	526.2	541.2	560.6
Longitud del Telescopio (mm)	100	115	130	150	170
Ángulo del Telescopio	70.0°	71.0°	72.0°	72.5°	72.5°
Rake (mm)	49	49	49	49	49
Trail (mm)	73.2	66.8	60.4	57.2	57.2
Distancia entre Ejes (mm)	969.9	974.7	977	984.1	999.3
Longitud de Vaina Inferior (mm)	405	405	405	405	405
Caída del Eje de Centro (mm)	72	72	70	70	70
Stack (mm)	494.1	511.8	527	547.8	566.9
Reach (mm)	365.6	372.9	377.8	382.9	392.1
Altura del Tubo Superior al Suelo (mm)	714.8	732.6	760.8	786.9	814
Ancho del Manubrio (mm)	360	380	380	400	420
Longitud de la Potencia (mm)	80	80	90	100	110
Longitud de la Biela (mm)	160	165	165	170	170

Todas las especificaciones están sujetas a cambios sin previo aviso.