

ENVILIV ADVANCED 2



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLORS	Midnight Pine
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact SL Aero, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
GRIPS	Liv Stratus Lite 2.0
STEM	Liv Contact SL Aero, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SEATPOST	Giant Vector, composite, -5/ +15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADDLE	Liv Alacra SL
DRIVETRAIN	
SHIFTERS	Shimano 105
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
BRAKES	Shimano 105 hydraulic, Shimano SM-RT64 [F]160mm, [R]140mm
BRAKE LEVERS	Shimano 105 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x36
CHAIN	KMC X12L-1
CRANKSET	Shimano 105, 36/52 XXS:160mm, XS:165mm, S:165mm, M:170mm, L:170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant P-A1 Disc, alloy
HUBS	Giant P-A1 Disc, 12mm thru-axle
SPOKES	stainless
TIRES	Giant Gavia Course, 700x28c, folding, tubeless
EXTRAS	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	446,5	465	498	528	558
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	504	514,8	526,2	541,2	560,6
Head Tube Length (mm)	100	115	130	150	170
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	73,2	66,8	60,4	57,2	57,2
Wheelbase (mm)	969,9	974,7	977	984,1	999,3
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	70
Stack (mm)	494,1	511,8	527	547,8	566,9
Reach (mm)	365,6	372,9	377,8	382,9	392,1
Stand Over Height (mm)	714,8	732,6	760,8	786,9	814
Handlebar Width (mm)	360	380	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	160	165	165	170	170

All specifications listed are subject to change without notice.