ENVILIV ADVANCED 2



SPECS

QUADRO	
TAMANHOS	XXS, XS, S, M, L
CORES	Midnight Pine, Desert Pearl
QUADRO	Advanced-grade composite, 12x142mm thru-axle, disc
FORQUILHA	Advanced-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
GUIADOR	Liv Contact SL Aero, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
PUNHOS	Liv Stratus Lite 2.0
AVANÇO	Liv Contact SL Aero, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
ESPIGÃO DE SELIM	Giant Vector, composite, -5/ +15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SELIM	Liv Alacra SL
TRANSMISSÃO	
MANETES	Shimano 105
DESVIADOR DIANTEIRO	Shimano 105
DESVIADOR TRASEIRO	Shimano 105
TRAVÕES	Shimano 105 hydraulic, Shimano SM-RT64 [F]160mm, [R]140mm
MANÍPULOS DOS TRAVÕES	Shimano 105 hydraulic
CASSETE	Shimano 105, 12-speed, 11x36
CORRENTE	KMC X12L-1
CONJUNTO PEDALEIRO	Shimano 105, 36/52 XXS:160mm, XS:165mm, S:165mm, M:170mm, L:17omm
MOVIMENTO CENTRAL	Shimano, press fit

RODAS	
AROS	Giant P-A1 Disc, alloy
CUBOS	Giant P-A1 Disc, 12mm thru-axle
RAIOS	stainless
PNEUS	Giant Gavia Course, 700x28c, folding, tubeless
EXTRAS	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

Preço: 2 599,00 €

GEOMETRIA

QUADRO	XXS	XS	S	M	L
Comprimento do tubo do assento (mm)	446,5	465	498	528	558
Ângulo do tubo do assento	75,0°	75,0°	74,5°	74,0°	73,5°
Comprimento do tubo superior (mm)	504	514,8	526,2	541,2	560,6
Comprimento do tubo principal (mm)	100	115	130	150	170
Ângulo do tubo principal	70,0°	71,0°	72,0°	72,5°	72,5°
Garfo ancinho (mm)	49	49	49	49	49
Trilha (mm)	73,2	66,8	60,4	57,2	57,2
distância entre eixos (mm)	969,9	974,7	977	984,1	999,3
Comprimento Chain Stay (mm)	405	405	405	405	405
Suporte inferior (mm)	72	72	70	70	70
Pilha (mm)	494,1	511,8	527	547,8	566,9
Alcançar (mm)	365,6	372,9	377,8	382,9	392,1
Altura do standover (mm)	714,8	732,6	760,8	786,9	814
Largura do guidão (mm)	360	380	380	400	420
Comprimento da haste (mm)	80	80	90	100	110
Comprimento da Manivela (mm)	160	165	165	170	170

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.