ENVILIV ADVANCED 2



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XXS, XS, S, M, L
BARVE	Midnight Pine, Desert Pearl
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc
VILICE	Advanced-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTE	
KRMILO	Liv Contact SL Aero, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
GRIPS	Liv Stratus Lite 2.0
OPORA KRMILA	Liv Contact SL Aero, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
OPORA SEDEŽA	Giant Vector, composite, -5/ +15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SEDEŽ	Liv Alacra SL
POGON	
PRESTAVNE ROČICE	Shimano 105
PREDNJI MENJALNIK	Shimano 105
ZADNJI MENJALNIK	Shimano 105
ZAVORE	Shimano 105 hydraulic, Shimano SM-RT64 [F]160mm, [R]140mm
ZAVORNE ROČICE	Shimano 105 hydraulic
VERIŽNIK	Shimano 105, 12-speed, 11x36
VERIGA	KMC X12L-1
GONILKE Z VERIŽNIKI	Shimano 105, 36/52 XXS:160mm, XS:165mm, S:165mm, M:170mm, L:17omm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant P-A1 Disc, alloy
PESTA	Giant P-A1 Disc, 12mm thru-axle
NAPERE	stainless
PLAŠČI	Giant Gavia Course, 700x28c, folding, tubeless
DODATKI	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dolžina sedežne cevi (mm)	446,5	465	498	528	558
Kot sedežne cevi	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	504	514,8	526,2	541,2	560,6
Višina glave okvirja (mm)	100	115	130	150	170
Krmilni kot	70,0°	71,0°	72,0°	72,5°	72,5°
Zamik vpetja osi (mm)	49	49	49	49	49
Trail (mm)	73,2	66,8	60,4	57,2	57,2
Medosna razdalja (mm)	969,9	974,7	977	984,1	999,3
Dolžina cevi ob verigi (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	494,1	511,8	527	547,8	566,9
Doseg (mm)	365,6	372,9	377,8	382,9	392,1
Višina zgornje cevi (mm)	714,8	732,6	760,8	786,9	814
Širina krmila (mm)	360	380	380	400	420
Dolžina opore krmila (mm)	80	80	90	100	110
Dolžina gonilke (mm)	160	165	165	170	170

Vse navedene specifikacije se lahko spremenijo brez obvestila.