ENVILIV ADVANCED 2



SPECS

RAM	
STORLEKAR	XS, S, M, L
FÄRGER	Midnight Pine
RAM	Advanced-grade composite, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Liv Contact SL Aero, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
GREPPAR	Liv Stratus Lite 2.0
STAM	Liv Contact SL Aero, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SADELSTOLPE	Giant Vector, composite, -5/ +15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADEL	Liv Alacra SL
DRIVLINA	
VÄXLAR	Shimano 105
FRAMVÄXEL	Shimano 105
BAKVÄXEL	Shimano 105
BROMSAR	Shimano 105 hydraulic, Shimano SM-RT64 [F]160mm, [R]140mm
BROMSSPAKAR	Shimano 105 hydraulic
KASSETT	Shimano 105, 12-speed, 11x36
KEDJA	KMC X12L-1
VEVPARTI	Shimano 105, 36/52 XXS:160mm, XS:165mm, S:165mm, M:170mm, L:17omm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant P-A1 Disc, alloy
NAV	Giant P-A1 Disc, 12mm thru-axle
EKRAR	stainless
DÄCK	Giant Gavia Course, 700x28c, folding, tubeless
EXTRAFUNKTIONER	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

Price: 35 990,00 kr

GEOMETRY

RAM	XS	S	M	L
Längd sadelrör (mm)	465	498	528	558
Vinkel sadelrör	75,0°	74,5°	74,0°	73,5°
Topprörets längd (mm)	514,8	526,2	541,2	560,6
Styrhuvud Längd (mm)	115	130	150	170
Vinkel styrhuvud	71,0°	72,0°	72,5°	72,5°
Gaffelvinkel (mm)	49	49	49	49
Spår (mm)	66,8	60,4	57,2	57,2
Hjulbas (mm)	974,7	977	984,1	999,3
Kedjestagslängd (mm)	405	405	405	405
Nedre fäste Drop (mm)	72	70	70	70
Stack (mm)	511,8	527	547,8	566,9
Reach (mm)	372,9	377,8	382,9	392,1
Stå över höjden (mm)	732,6	760,8	786,9	814
Styrets bredd (mm)	380	380	400	420
Stamlängd (mm)	80	90	100	110
Vevlängd (mm)	165	165	170	170

All specifications listed are subject to change without notice.