ENVILIV ADVANCED 2



產品規格

車架	
尺寸	XXS, XS, S,
顏色	Desert Pearl 珍珠金沙
車架	Advanced-grade composite, 12x142mm thru-axle, disc
前叉	Advanced-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
車把手	Liv Contact SL Aero, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm,
把手帶/套	Liv Stratus Lite 2.0
豎桿	Liv Contact SL Aero, -10-degree XXS: 80mm, XS: 80mm, S: 90mm
座桿	Giant Vector, composite, -5/ +15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
坐墊	Liv Alacra SL
DRIVETRAIN	
變速把手	Shimano 105
前變速器	Shimano 105
後變速器	Shimano 105
煞車系統	Shimano 105 hydraulic, Shimano SM-RT64 [F]160mm, [R]140mm
煞車把手	Shimano 105 hydraulic
飛輪	Shimano 105, 12-speed, 11x36
鍊條	KMC X12L-1
大齒盤	Shimano 105, 36/52 XXS:160mm, XS:165mm, S:165mm
BOTTOM BRACKET (B B)	Shimano, press fit

輪組	
輪圈	Giant P-A1 Disc, alloy
花鼓	Giant P-A1 Disc, 12mm thru-axle
輻條	stainless
外胎	Giant Gavia Course, 700x28c, folding, tubeless
其他	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

Price: NT$78,800

車架幾何

車架	XXS	XS	S
座(立)管長 (mm)	446.5	465	498
座(立)管角度	75.0°	75.0°	74.5°
上管長度 (mm)	504	514.8	526.2
頭管長度 (mm)	100	115	130
頭管角度	70.0°	71.0°	72.0°
前叉 (mm)	49	49	49
Trail (mm)	73.2	66.8	60.4
前後輪距 (mm)	969.9	974.7	977
後下叉長度 (mm)	405	405	405
五通下降高度 (mm)	72	72	70
頭碗至五通高度 (mm)	494.1	511.8	527
頭碗至五通長度 (mm)	365.6	372.9	377.8
上管至地面高度 (mm)	714.8	732.6	760.8
把手寬 (mm)	360	380	380
龍頭長度 (mm)	80	80	90
曲柄長度 (mm)	160	165	165

＊捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。