

ENVILIV ADVANCED PRO 0 AXS



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Gloss Ocean Twilight/Carbon Smoke/Gold Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Contact SLR Aero, 31.8mm
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact SL Aero
SEATPOST	Giant Vector, composite
SADDLE	Liv Alcara SL
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	SRAM Force eTap AXS 2x12
FRONT DERAILLEUR	SRAM Force eTap AXS
REAR DERAILLEUR	SRAM Force eTap AXS
BRAKES	SRAM Force eTap AXS hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM Force, 12-speed, 10x33
CHAIN	SRAM Force D1
CRANKSET	SRAM Force D2 DUB, 35/48 with power meter
BOTTOM BRACKET	SRAM, press fit

WHEELS	
RIMS	Giant SLR 1 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	SAPIM CX-Ray
TYRES	CADEX Race 25, tubeless, 700x25c (26.5mm), folding
EXTRAS	Out front computer mount, two bottle cages, factory tubeless set up, 30mm max tyre size
LIMITS	
MAX TYRE CLEARANCE	30mm

Price: £6,499.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	470	500	530
Seat Tube Angle	75.0°	74.5°	74.0°
Top Tube Length (mm)	508	524	540
Head Tube Length (mm)	120	135	155
Head Tube Angle	71.0°	72.0°	72.5°
Fork Rake (mm)	49	49	49
Trail (mm)	66.3	59.9	56.8
Wheelbase (mm)	973	977	984
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	72	70	70
Stack (mm)	517	532	553
Reach (mm)	370	377	382
Stand Over Height (mm)	731.8	761.1	787.4
Handlebar Width (mm)	360	380	400
Stem Length (mm)	80	90	100
Crank Length (mm)	165	170	170
Wheel Size	700C	700C	700C

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.