ENVILIV ADVANCED PRO 0



SPECS

ΣΚΕΛΕΤΌΣ	
ΜΕΓΈΘΗ	XXS, XS, S, M, L
ΧΡΏΜΑΤΑ	Iron Rouge/Chrome
ΣΚΕΛΕΤΌΣ	Advanced-grade composite, 12x142mm thru-axle, disc
ΠΙΡΟΎΝΙ	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ΑΝΆΡΤΗΣΗ	N/A
ΕΞΑΡΤΉΜΑΤΑ	
ΤΙΜΌΝΙ	Liv Contact SLR Aero, 31.8mm, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
ΛΑΙΜΌΣ ΤΙΜΟΝΙΟΎ	Giant Contact SL Aero, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
ΛΑΙΜΌΣ ΣΈΛΛΑΣ	Giant Vector, composite, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
ΣΈΛΛΑ	Liv Alacra SL
ΜΕΤΆΔΟΣΗ	
ΛΕΒΙΈ ΤΑΧΥΤΉΤΩΝ	Shimano Ultegra Di2 ST-R8170
ΝΤΕΡΑΓΙΈΡ ΕΜΠΡΌΣΘΙΟ	Shimano Ultegra Di2 FD-R8150
ΝΤΕΡΑΓΙΈΡ ΟΠΊΣΘΙΟ.	Shimano Ultegra Di2 RD-R8150
ΦΡΈΝΑ	Shimano Ultegra hydraulic, Shimano rotors, [F]160mm, [R]140mm
ΜΑΝΈΤΤΕΣ ΦΡΈΝΩΝ	Shimano Ultegra hydraulic
CASETTE Ή ΕΛΕΎΘΕΡΟ	Shimano Ultegra, 12-speed, 11x30
ΑΛΥΣΊΔΑ	KMC X12
ΔΙΣΚΟΒΡΑΧΊΩΝΑΣ	Shimano Ultegra, 36/52 with Giant Power Pro power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
ΣΤΕΦΆΝΙΑ	Giant SLR 1 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
ΚΈΝΤΡΑ	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
ΑΚΤΊΝΕΣ	SAPIM CX-Ray
ΕΛΑΣΤΙΚΆ	CADEX Road Race GC, tubeless, 700x28c, folding
EXTRAS	computer mount, two bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΌΣ	XXS	XS	S	M	L
Seat Tube Length (mm)	440	470	500	530	560
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	72,7	66,3	59,9	56,8	56,8
Wheelbase (mm)	970	973	977	984	996
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	67
Stack (mm)	499	517	532	553	569
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	706	732	761	787	815
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	160	165	165	170	172,5

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση