ENVILIV ADVANCED PRO 0



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLOURS	Ocean Twilight/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Contact SLR Aero, 31.8mm XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact SL Aero XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SEATPOST	Giant Vector, composite XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADDLE	Liv Alcara SL
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2 ST-R8170
FRONT DERAILLEUR	Shimano Ultegra Di2 FD-R8150
REAR DERAILLEUR	Shimano Ultegra Di2 RD-R8150
BRAKES	Shimano Ultegra hydraulic, Shimano rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Ultegra hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x30
CHAIN	KMC X12
CRANKSET	Shimano Ultegra, 36/52 with Giant PowerPro power meter XXS:165mm, XS:165mm, S:170mm, M:170mm, L:172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 1 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	SAPIM CX-Ray
TIRES	CADEX Race 25, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, two bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

Suggested Retail Price (CDN): $7,699.00

FRAME GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	440	470	500	530	560
Seat Tube Angle	75.0°	75.0°	74.5°	74.0°	73.5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70.0°	71.0°	72.0°	72.5°	72.5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	72.7	66.3	59.9	56.8	56.8
Wheelbase (mm)	970	973	977	984	996
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	67
Stack (mm)	499	517	532	553	569
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	706.1	731.8	761.1	787.4	815.3
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	165	165	170	170	172.5
Wheel Size	700C	700C	700C	700C	700C

All prices and specifications are subject to change without notice.