

ENVILIV ADVANCED PRO 0



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Gloss Ocean Twilight/Carbon Smoke/Gold Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Contact SLR Aero, 31.8mm
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact SL Aero
SEATPOST	Giant Vector, composite
SADDLE	Liv Alcara SL
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2 ST-R8170 2x12
FRONT DERAILLEUR	Shimano Ultegra Di2 FD-R8150
REAR DERAILLEUR	Shimano Ultegra Di2 RD-R8150
BRAKES	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Ultegra Di2 hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x30
CHAIN	KMC X12
CRANKSET	Shimano Ultegra, 36/52, with Giant Power Pro power meter
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 1 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	SAPIM CX-Ray
TYRES	CADEX Race 25, tubeless, 700x25c (26.5mm), folding
EXTRAS	Out front computer mount, two bottle cages, factory tubeless set up
LIMITS	
MAX TIRE CLEARANCE	32mm

Price: €7,249.00

GEOMETRY

FRAME	S
Seat Tube Length (mm)	500
Seat Tube Angle	74.5°
Top Tube Length (mm)	524
Head Tube Length (mm)	135
Head Tube Angle	72.0°
Fork Rake (mm)	49
Trail (mm)	59.9
Wheelbase (mm)	977
Chain Stay Length (mm)	405
Bottom Bracket Drop (mm)	70
Stack (mm)	532
Reach (mm)	377
Stand Over Height (mm)	761.1
Handlebar Width (mm)	380
Stem Length (mm)	90
Crank Length (mm)	170
Wheel Size	700C

All specifications listed are subject to change without notice.