

# ENVILIV ADVANCED PRO 0



## SPECS

FRAME	
<b>SIZES</b>	XXS, XS, S, M, L
<b>COLORS</b>	Iron Rouge/Chrome
<b>FRAME</b>	Advanced-grade composite, 12x142mm thru-axle, disc
<b>FORK</b>	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Liv Contact SLR Aero, 31.8mm, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
<b>GRIPS</b>	Liv Stratus Elite 2.0
<b>STEM</b>	Giant Contact SL Aero, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
<b>SEATPOST</b>	Giant Vector, composite, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
<b>SADDLE</b>	Liv Alacra SL
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Ultegra Di2 ST-R8170
<b>FRONT DERAILLEUR</b>	Shimano Ultegra Di2 FD-R8150
<b>REAR DERAILLEUR</b>	Shimano Ultegra Di2 RD-R8150
<b>BRAKES</b>	Shimano Ultegra hydraulic, Shimano rotors, [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	Shimano Ultegra hydraulic
<b>CASSETTE</b>	Shimano Ultegra, 12-speed, 11x30
<b>CHAIN</b>	KMC X12
<b>CRANKSET</b>	Shimano Ultegra, 36/52 with Giant Power Pro power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant SLR 1 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
<b>HUBS</b>	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	SAPIM CX-Ray
<b>TIRES</b>	CADEX Road Race GC, tubeless, 700x28c, folding
<b>EXTRAS</b>	computer mount, two bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	32mm

## GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	440	470	500	530	560
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	72,7	66,3	59,9	56,8	56,8
Wheelbase (mm)	970	973	977	984	996
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	67
Stack (mm)	499	517	532	553	569
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	706	732	761	787	815
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	160	165	165	170	172,5

All specifications listed are subject to change without notice.