

ENVILIV ADVANCED SL 0-RED



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, L
FARVER	Prism Pearl
RAMME	Advanced SL-grade composite, 12x142mm thru-axle, integrated seatpost, disc
FORGAFFEL	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYR	Liv Contact SLR 0 Aero Integrated, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
GREB / STYRBÅND	Liv Stratus Lite 2.0
FREMPIND	Liv Contact SLR 0 Aero Integrated, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SADELPIND	Advanced SL-grade composite, integrated design, -5/+15mm offset
SADEL	CADEX Amp 155
GEARGRUPPE	
SKIFTEGREB	SRAM RED AXS HRD
FORSKIFTER	SRAM RED AXS FD-RED-E-E1
BAGSKIFTER	SRAM RED AXS FD-RED-E-E1
BREMSE	SRAM RED eTap hydraulic, PaceLine X rotors [F] 160mm, [R] 140mm
BREMSEGREB	SRAM RED AXS HRD
KASSETTE	SRAM RED, 12-speed, 10x36
KÆDE	SRAM RED E1 CN-RED-E1
KRANKSÆT	SRAM RED AXS, 35/48 with power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
KRANKBOKS	SRAM DUB ceramic, press fit

HJUL	
FÆLGE	CADEX Max 50 WheelSystem, [F] 50mm, [R] 50mm
NAV	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, ceramic bearings [R] CADEX R3-C48 Aero Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
EGER	CADEX Super Aero Carbon
DÆK	CADEX Aero, tubeless, 700x28c, folding
EKSTRA	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

Pris: 98.999,00 kr.

GEOMETRI

RAMME	XS	S	M	L
Sadelrørslængde (mm)	680	710	740	770
Sadelrørsvinkel	75,0°	74,5°	74,0°	73,5°
Overrørslængde (mm)	514,8	526,2	541,2	560,6
Kronrørslængde (mm)	115	130	150	170
Kronrørsvinkel	71,0°	72,0°	72,5°	72,5°
Forgaffel fremspring (rake) (mm)	49	49	49	49
Sti (mm)	66,8	60,4	57,2	57,2
Akselafstand (mm)	974,7	977	984,1	999,3
Kædestagslængde (mm)	405	405	405	405
Krankboks drop (mm)	72	70	70	70
Stack (mm)	511,8	527	547,8	566,9
Reach (mm)	372,9	377,8	382,9	392,1
Skridthøjde (mm)	732,6	760,8	786,9	814
Styrbredde (mm)	380	380	400	420
Frempindslængde (mm)	80	90	100	110
Pedalarmslængde (mm)	165	165	170	170

Alle de anførte specifikationer kan ændres uden varsel.