

ENVILIV ADVANCED SL 0-RED



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLORS	Prism Pearl
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact SLR 0 Aero Integrated, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
GRIPS	Liv Stratus Lite 2.0
STEM	Liv Contact SLR 0 Aero Integrated, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SEATPOST	Advanced SL-grade composite, integrated design, -5/+15mm offset
SADDLE	CADEX Amp 155
DRIVETRAIN	
SHIFTERS	SRAM RED AXS HRD
FRONT DERAILLEUR	SRAM RED AXS FD-RED-E-E1
REAR DERAILLEUR	SRAM RED AXS FD-RED-E-E1
BRAKES	SRAM RED eTap hydraulic, PaceLine X rotors [F] 160mm, [R] 140mm
BRAKE LEVERS	SRAM RED AXS HRD
CASSETTE	SRAM RED, 12-speed, 10x36
CHAIN	SRAM RED E1 CN-RED-E1
CRANKSET	SRAM RED AXS, 35/48 with power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

WHEELS	
RIMS	CADEX Max 50 WheelSystem, [F] 50mm, [R] 50mm
HUBS	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, ceramic bearings [R] CADEX R3-C48 Aero Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	CADEX Super Aero Carbon
TIRES	CADEX Aero, tubeless, 700x28c, folding
EXTRAS	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	650	680	710	740	770
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	504	514,8	526,2	541,2	560,6
Head Tube Length (mm)	100	115	130	150	170
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	73,2	66,8	60,4	57,2	57,2
Wheelbase (mm)	969,9	974,7	977	984,1	999,3
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	70
Stack (mm)	494,1	511,8	527	547,8	566,9
Reach (mm)	365,6	372,9	377,8	382,9	392,1
Stand Over Height (mm)	714,8	732,6	760,8	786,9	814
Handlebar Width (mm)	360	380	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	160	165	165	170	170

All specifications listed are subject to change without notice.