

ENVILIV ADVANCED SL 0-RED



TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, L
VÄRIT	Prism Pearl
RUNKO	Advanced SL-grade composite, 12x142mm thru-axle, integrated seatpost, disc
HAARUKKA	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMONENTIT	
OHJAUSTANKO	Liv Contact SLR 0 Aero Integrated, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
GRIPIT	Liv Stratus Lite 2.0
OHJAINKANNATIN	Liv Contact SLR 0 Aero Integrated, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SATULATOLPPA	Advanced SL-grade composite, integrated design, -5/+15mm offset
SATULA	CADEX Amp 155
VOIMANSIIRTO	
VAIHDEVIPU	SRAM RED AXS HRD
ETUVAIHTAJA	SRAM RED AXS FD-RED-E-E1
TAKAVAIHTAJA	SRAM RED AXS FD-RED-E-E1
JARRUT	SRAM RED eTap hydraulic, PaceLine X rotors [F] 160mm, [R] 140mm
JARRUKAHVAT	SRAM RED AXS HRD
RATASPAKKA	SRAM RED, 12-speed, 10x36
KETJUT	SRAM RED E1 CN-RED-E1
KAMPISARJA	SRAM RED AXS, 35/48 with power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
KESKIÖ	SRAM DUB ceramic, press fit

RENKAAT	
VANTEET	CADEX Max 50 WheelSystem, [F] 50mm, [R] 50mm
NAVAT	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, ceramic bearings [R] CADEX R3-C48 Aero Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
PINNAT	CADEX Super Aero Carbon
RENKAAT	CADEX Aero, tubeless, 700x28c, folding
LISÄTIEDOT	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

Suositus hinta: 13 299,00 €

GEOMETRIA

RUNKO	XS	S	M	L
Satulaputken pituus (mm)	680	710	740	770
Satulaputken kulma	75,0°	74,5°	74,0°	73,5°
Vaakaputken pituus (mm)	514,8	526,2	541,2	560,6
Emäputken pituus (mm)	115	130	150	170
Emäputken kulma	71,0°	72,0°	72,5°	72,5°
Haarukan offset (mm)	49	49	49	49
Trail-mitta (mm)	66,8	60,4	57,2	57,2
Akseliväli (mm)	974,7	977	984,1	999,3
Takahaarukan alaputken pituus (mm)	405	405	405	405
Keskiön pudotus (mm)	72	70	70	70
Stack-mitta (mm)	511,8	527	547,8	566,9
Reach-mitta (mm)	372,9	377,8	382,9	392,1
Standover-mitta (mm)	732,6	760,8	786,9	814
Ohjaustangon leveys (mm)	380	380	400	420
Ohjainkannattimen pituus (mm)	80	90	100	110
Kammen pituus (mm)	165	165	170	170

Kaikki ilmoitettut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.