ENVILIV ADVANCED SL 0 RED



TECHNIQUES

CADRE	
TAILLES	XXS, XS, S, M, L
COLORIS	Prism Pearl
CADRE	Advanced SL-grade composite, 12x142mm thru-axle, integrated seatpost, disc
FOURCHE	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPOSANTS	
CINTRE	Liv Contact SLR 0 Aero Integrated, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
POIGNÉES	Liv Stratus Lite 2.0
POTENCE	Liv Contact SLR 0 Aero Integrated, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
TIGE DE SELLE	Advanced SL-grade composite, integrated design, -5/+15mm offset
SELLE	CADEX Amp 155mm
DÉRAILLEUR	
MANETTES	SRAM RED AXS HRD
DÉRAILLEUR AVANT	SRAM RED AXS FD-RED-E-E1
DÉRAILLEUR ARRIÈRE	SRAM RED AXS FD-RED-E-E1
FREINS	SRAM RED eTap hydraulic, PaceLine X rotors [F] 160mm, [R] 140mm
LEVIERS DE FREIN	SRAM RED AXS HRD
CASSETTE	SRAM RED, 12-speed, 10x36
CHAÎNE	SRAM RED E1 CN-RED-E1
PÉDALIER	SRAM RED AXS, 35/48 with Quark power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
BOITIER DE PÉDALIER	SRAM DUB ceramic, press fit

ROUES	
JANTES	CADEX Max 50 WheelSystem, [F] 50mm, [R] 50mm
MOYEUX	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, ceramic bearings [R] CADEX R3-C48 Aero Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
RAYONS	CADEX Super Aero Carbon
PNEUS	CADEX Aero, tubeless, 700x28c, folding, 240 TPI
EXTRAS	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 12 400,00 €

GÉOMÉTRIE

CADRE	XXS	XS	S	M	L
Longueur de tube de selle (mm)	650	680	710	740	770
Angle de tube de selle	75,0°	75,0°	74,5°	74,0°	73,5°
Longueur du tube supérieur (mm)	504	514,8	526,2	541,2	560,6
Longueur du tube de direction (mm)	100	115	130	150	170
Angle du tube de direction	70,0°	71,0°	72,0°	72,5°	72,5°
Déport de fourche (mm)	49	49	49	49	49
Trail (mm)	73,2	66,8	60,4	57,2	57,2
Empattement (mm)	969,9	974,7	977	984,1	999,3
Longueur des bases (mm)	405	405	405	405	405
Drop du boitier de pédalier (mm)	72	72	70	70	70
Stack (mm)	494,1	511,8	527	547,8	566,9
Reach (mm)	365,6	372,9	377,8	382,9	392,1
Hauteur en statique (mm)	714,8	732,6	760,8	786,9	814
Largeur de cintre (mm)	360	380	380	400	420
Longueur de potence (mm)	80	80	90	100	110
Longueur des manivelles (mm)	160	165	165	170	170

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.