

ENVILIV ADVANCED SL 0-RED



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Prism Pearl
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, integrated seatpost, disc
VOORVORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ONDERDELEN	
STUUR	Liv Contact SLR 0 Aero Integrated, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
HANDVATTEN	Liv Stratus Lite 2.0
STUURPEN	Liv Contact SLR 0 Aero Integrated, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
ZADEL	Advanced SL-grade composite, integrated design, -5/+15mm offset
ZADEL	CADEX Amp 155
AFMONTAGE	
SHIFTERS	SRAM RED AXS HRD
VOORDERAILLEUR	SRAM RED AXS FD-RED-E-E1
ACHTERDERAILLEUR	SRAM RED AXS FD-RED-E-E1
REMMEN	SRAM RED eTap hydraulic, PaceLine X rotors [F] 160mm, [R] 140mm
REMHENDELS	SRAM RED AXS HRD
CASSETTE	SRAM RED, 12-speed, 10x36
AANDRIJVING	SRAM RED E1 CN-RED-E1
CRANKSET	SRAM RED AXS, 35/48 with power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

WIELSET	
VELGEN	CADEX Max 50 WheelSystem, [F] 50mm, [R] 50mm
NAVEN	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, ceramic bearings [R] CADEX R3-C48 Aero Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	CADEX Super Aero Carbon
BANDEN	CADEX Aero, tubeless, 700x28c, folding
EXTRA'S	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

Adviesprijs: € 12.499,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis lengte (mm)	680	710	740	770
Zitbuis hoek	75,0°	74,5°	74,0°	73,5°
Frame Lengte (horizontaal) (mm)	514,8	526,2	541,2	560,6
Balhoofdbuis Lengte (mm)	115	130	150	170
Balhoofdbuis Hoek	71,0°	72,0°	72,5°	72,5°
Vork Sprong (mm)	49	49	49	49
Naloop (mm)	66,8	60,4	57,2	57,2
Wielbasis (mm)	974,7	977	984,1	999,3
Liggende achtervork lengte (mm)	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	70
Stack (mm)	511,8	527	547,8	566,9
Reach (mm)	372,9	377,8	382,9	392,1
Stand Over Height (mm)	732,6	760,8	786,9	814
Stuur breedte (mm)	380	380	400	420
Stuurpen Lengte (mm)	80	90	100	110
Cranklengte (mm)	165	165	170	170

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.