

ENVILIV ADVANCED SL 1



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLORS	Raw Carbon
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact SLR 0 Aero Integrated, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
GRIPS	Liv Stratus Lite 2.0
STEM	Liv Contact SLR 0 Aero Integrated, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SEATPOST	Advanced SL-grade composite, integrated design, -5/+15mm offset
SADDLE	Liv Alacra SLR
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2 ST-R8170
FRONT DERAILLEUR	Shimano Ultegra Di2 FD-R8150
REAR DERAILLEUR	Shimano Ultegra Di2 RD-R8150
BRAKES	Shimano Ultegra hydraulic, Shimano rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Ultegra hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CHAIN	Shimano Ultegra, CN-M8100
CRANKSET	Shimano Ultegra, 36/52 with Giant Power Pro power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 0 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
HUBS	[F] Giant Aero Hub, CenterLock, 12mm thru-axle [R] Giant Aero Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Super Aero Carbon
TIRES	CADEX Aero, tubeless, 700x28c, folding
EXTRAS	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	650	680	710	740	770
Seat Tube Angle	75.0°	75.0°	74.5°	74.0°	73.5°
Top Tube Length (mm)	504	514.8	526.2	541.2	560.6
Head Tube Length (mm)	100	115	130	150	170
Head Tube Angle	70.0°	71.0°	72.0°	72.5°	72.5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	73.2	66.8	60.4	57.2	57.2
Wheelbase (mm)	969.9	974.7	977	984.1	999.3
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	70
Stack (mm)	494.1	511.8	527	547.8	566.9
Reach (mm)	365.6	372.9	377.8	382.9	392.1
Stand Over Height (mm)	714.8	732.6	760.8	786.9	814
Handlebar Width (mm)	360	380	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	160	165	165	170	170

All specifications listed are subject to change without notice.