

ENVILIV ADVANCED SL



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Gloss Mercury/Carbon Smoke/Chrome
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Contact SLR Aero, 31.8mm
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact SLR Aero
SEATPOST	Giant Vector SLR, full-composite
SADDLE	CADEX Amp
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	SRAM RED eTap AXS 2x12
FRONT DERAILLEUR	SRAM RED eTap AXS
REAR DERAILLEUR	SRAM RED eTap AXS
BRAKES	SRAM RED eTap hydraulic, SRAM PaceLine X rotors [F] 160mm, [R] 140mm
BRAKE LEVERS	SRAM RED eTap AXS hydraulic
CASSETTE	SRAM RED, 12-speed, 10x33
CHAIN	SRAM RED
CRANKSET	SRAM RED PM E1 DUB, 35/48 with power meter
BOTTOM BRACKET	SRAM, press fit

WHEELS	
RIMS	CADEX 50 Ultra WheelSystem, [F] 50mm, [R] 50mm
HUBS	[F] CADEX R3-C Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C40 Aero Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	CADEX Aero Carbon Spoke
TYRES	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	Out front computer mount, two bottle cages, factory tubeless set up, 30mm max tyre size
LIMITS	
MAX TYRE CLEARANCE	30mm

Price: £11,999.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	470	500	530
Seat Tube Angle	75.0°	74.5°	74.0°
Top Tube Length (mm)	508	524	540
Head Tube Length (mm)	120	135	155
Head Tube Angle	71.0°	72.0°	72.5°
Fork Rake (mm)	49	49	49
Trail (mm)	66.3	59.9	56.8
Wheelbase (mm)	973	977	984
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	72	70	70
Stack (mm)	517	532	553
Reach (mm)	370	377	382
Stand Over Height (mm)	731.8	761.1	787.4
Handlebar Width (mm)	360	380	400
Stem Length (mm)	80	90	100
Crank Length (mm)	165	170	170
Wheel Size	700C	700C	700C

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.