ENVILIV ADVANCED SL LTD



SPECS

RAMME	
STØRRELSE	XXS, XS, S, M, L
FARGE	Blanc Collection
RAMME	Advanced SL-grade composite, 12x142mm thru-axle, disc
GAFFEL	Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, 12x100mm, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Liv Contact SLR Aero, 31.8mm XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv All Condition
STYRSTEM	Giant Contact SLR Aero XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SETEPINNE	Giant Vector SLR, full-composite XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADEL	Liv Alcara SLR
PEDALER	N/A
DRIVVERK	
GIRHENDLER	SRAM Force eTap AXS
FRONTGIR	SRAM Force eTap AXS
BAKGIR	SRAM Force eTap AXS
BREMSER	SRAM Force eTap AXS hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
BREMSEHENDLER	SRAM Force eTap AXS hydraulic
KASSETT	SRAM Force, 12-speed, 10x28
KJEDE	SRAM Force D1
KRANK	SRAM Force D2 DUB, 35/48 with Quarq power meter XXS:165mm, XS:165mm, S:170mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	CADEX 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
NAV	[F] CADEX R3-C40 Aero Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C40 Aero Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
EIKE	CADEX Super Aero Carbon Spoke
DEKK	CADEX Race, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, two bottle cages, tubeless prepared, 30mm max tire size

GEOMETRI

RAMME	XXS	XS	S	M	L
Seat Tube Length (mm)	440	470	500	530	560
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	72,7	66,3	59,9	56,8	56,8
Wheelbase (mm)	970	973	977	984	996
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	67
Stack (mm)	499	517	532	553	569
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	706,1	731,8	761,1	787,4	815,3
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	165	165	170	170	172,5
Wheel Size	700C	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.