ENVILIV ADVANCED SL LTD



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XXS, XS, S, M, L
BARVE	Blanc Collection
OKVIR	Advanced SL-grade composite, 12x142mm thru-axle, disc
VILICE	Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, 12x100mm, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Liv Contact SLR Aero, 31.8mm XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv All Condition
OPORA KRMILA	Giant Contact SLR Aero XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
OPORA SEDEŽA	Giant Vector SLR, full-composite XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SEDEŽ	Liv Alcara SLR
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM Force eTap AXS
PREDNJI MENJALNIK	SRAM Force eTap AXS
ZADNJI MENJALNIK	SRAM Force eTap AXS
ZAVORE	SRAM Force eTap AXS hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
ZAVORNE ROČICE	SRAM Force eTap AXS hydraulic
VERIŽNIK	SRAM Force, 12-speed, 10x28
VERIGA	SRAM Force D1
GONILKE Z VERIŽNIKI	SRAM Force D2 DUB, 35/48 with Quarq power meter XXS:165mm, XS:165mm, S:170mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	CADEX 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
PESTA	[F] CADEX R3-C40 Aero Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C40 Aero Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
NAPERE	CADEX Super Aero Carbon Spoke
PLAŠČI	CADEX Race, tubeless, 700x25c (26.5mm), folding
DODATKI	computer mount, two bottle cages, tubeless prepared, 30mm max tire size

GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dolžina sedežne cevi (mm)	440	470	500	530	560
Kot sedežne cevi	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Višina glave okvirja (mm)	105	120	135	155	175
Krmilni kot	70,0°	71,0°	72,0°	72,5°	72,5°
Zamik vpetja osi (mm)	49	49	49	49	49
Trail (mm)	72,7	66,3	59,9	56,8	56,8
Medosna razdalja (mm)	970	973	977	984	996
Dolžina cevi ob verigi (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	67
Oddaljenost zgornje cevi od gonilne osi (mm)	499	517	532	553	569
Doseg (mm)	364	370	377	382	386
Višina zgornje cevi (mm)	706,1	731,8	761,1	787,4	815,3
Širina krmila (mm)	360	360	380	400	420
Dolžina opore krmila (mm)	80	80	90	100	110
Dolžina gonilke (mm)	165	165	170	170	172,5
Velikost obročnikov	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.