

# ENVILIV ADVANCED SL TEAM



## SPECS

RAMME	
STØRRELSE	XXS, XS, S, M, L
FARGE	Maraya Aubergine
RAMME	Advanced SL-grade composite, 12x142mm thru-axle, disc
GAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Liv Contact SLR Aero, 31.8mm, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
STYRSTEM	Giant Contact SLR Aero, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SETEPINNE	Giant Vector SLR, full-composite, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADEL	CADEX Amp
DRIVVERK	
GIRHENDLER	SRAM RED AXS
FRONTGIR	SRAM RED AXS
BAKGIR	SRAM RED AXS
BREMSER	SRAM RED eTap hydraulic, SRAM PaceLine X rotors, [F] 160mm, [R] 140mm
BREMSEHENDLER	SRAM RED AXS
KASSETT	SRAM RED, 12-speed, 10x33
KJEDE	SRAM RED
KRANK	SRAM RED AXS, 35/48 with power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

HJUL	
FELG	CADEX Ultra 50 WheelSystem, [F] 50mm, [R] 50mm
NAV	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C40 Aero Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
EIKE	CADEX Aero Carbon Spoke
DEKK	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, two bottle cages, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

## GEOMETRI

RAMME	XXS	XS	S	M	L
Seat Tube Length (mm)	440	470	500	530	560
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	72,7	66,3	59,9	56,8	56,8
Wheelbase (mm)	970	973	977	984	996
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	67
Stack (mm)	499	517	532	553	569
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	706,1	731,8	761,1	787,4	815,3
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	165	165	170	170	172,5
Wheel Size	700C	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.