

# ENVILIV ADVANCED SL TEAM



## SPECS

FRAME	
<b>SIZES</b>	XXS, XS, S, M, L
<b>COLORS</b>	Maraya Aubergine
<b>FRAME</b>	Advanced SL-grade composite, 12x142mm thru-axle, disc
<b>FORK</b>	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Liv Contact SLR Aero, 31.8mm, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
<b>GRIPS</b>	Liv Stratus Elite 2.0
<b>STEM</b>	Giant Contact SLR Aero, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
<b>SEATPOST</b>	Giant Vector SLR, full-composite, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
<b>SADDLE</b>	CADEX Amp
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM RED AXS
<b>FRONT DERAILLEUR</b>	SRAM RED AXS
<b>REAR DERAILLEUR</b>	SRAM RED AXS
<b>BRAKES</b>	SRAM RED eTap hydraulic, SRAM PaceLine X rotors, [F] 160mm, [R] 140mm
<b>BRAKE LEVERS</b>	SRAM RED AXS
<b>CASSETTE</b>	SRAM RED, 12-speed, 10x33
<b>CHAIN</b>	SRAM RED
<b>CRANKSET</b>	SRAM RED AXS, 35/48 with power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm
<b>BOTTOM BRACKET</b>	SRAM DUB ceramic, press fit

WHEELS	
<b>RIMS</b>	CADEX Ultra 50 WheelSystem, [F] 50mm, [R] 50mm
<b>HUBS</b>	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C40 Aero Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	CADEX Aero Carbon Spoke
<b>TIRES</b>	CADEX Aero, tubeless, 700x25c (26.5mm), folding
<b>EXTRAS</b>	computer mount, two bottle cages, tubeless prepared, 30mm max tire size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	30mm

## GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	440	470	500	530	560
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	72,7	66,3	59,9	56,8	56,8
Wheelbase (mm)	970	973	977	984	996
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	67
Stack (mm)	499	517	532	553	569
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	706,1	731,8	761,1	787,4	815,3
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	165	165	170	170	172,5
Wheel Size	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.